www.emos.eu

Order Code Item Numbe Packaging Type

product: camera unit with RFID = number of buttons on the camera unit: 2 = power supply: via monitor = number of wiress (monitor/lock/power supply): 2×4/2/0 = dimensions of the camera unit: 135 × 50 × 25 mm = IP rating: IP44 = camera viewing angle: 160° = door lock control = installation: surface = packaging: 1 pc, box















H3017 30 10 003 017 1/-/-/20 EM-10AHD RF-2

product: camera unit with RFID = number of buttons on the camera unit: 4 = power supply: via monitor = number of wiress (monitor/lock/power supply): $4 \times 4/2/0$ = dimensions of the camera unit: $135 \times 50 \times 25$ mm = IP rating: IP44 = camera viewing angle: 160° = door lock control = installation: surface = packaging: 1 pc, box

















H3018

1/-/-/20

30 10 003 018 EM-10AHD RF-4

screen size: 7" = lock/gate control: yes/yes = power supply for the screen: 14.5 V DC (includedí) = number of wires (monitor/lock/gate): 2+0+0 = monitor size: $152 \times 215 \times 18$ mm = dimensions of the camera unit: $141 \times 63 \times 40$ mm = camera viewing angle: 80° = packaging: 1 pc, box























H2050 30 10 002 050 1/-/-/4 H2050

product: doorphone set with WiFi = screen size: 7" = lock/gate control: yes/yes = power supply for the screen: 12 V DC (included) = number of wires (monitor/lock/gate): 4+2+2 = monitor size: 215 × 20 × 150 mm = dimensions of the camera unit: 50 × 47 × 130 mm = camera viewing angle: 70° = packaging: 1 pc, box













8 592920 046852

H2014 30 10 000 121 1/-/-/4 EM-101WIFI

product: IP Door camera unit = number of buttons on the camera unit: 1 = power supply: 12 V DC (part of the package) = number of wiress (monitor/lock/power supply): UTP = dimensions of the camera unit: $80 \times 156 \times 63$ mm = IP rating: IP44 = camera viewing angle: 70° = door lock control = installation: surface = packaging: 1 pc, box















H113930 10 001 139

1/-/-/10 EM-102WIFI