



DC voltage: 6-400 V = AC voltage: 6-400 V = AC/DC voltage: 6 V, 12 V, 24 V, 50 V, 120 V, 230 V, 400 V = polarity indication = signalization: optical = power source: from power source = frequency range: 0-60 Hz = packaging: 1 pc, blister




M0003A 1/-/20/40
22 01 009 000 GK-9

DC voltage: 12-600 V = AC voltage: 12-600 V = AC/DC voltage: 12 V, 24 V, 50 V, 120 V, 230 V, 400 V, 600 V = polarity indication = signalization: optical = power source: from power source = frequency range: 0-60 Hz = packaging: 1 pc, blister



M0004A 1/-/-/40
22 01 010 000 VT-220

DC voltage: 12-400 V = AC voltage: 12-400 V = AC/DC voltage: 12 V, 24 V, 50 V, 120 V, 230 V, 400 V = polarity indication = phase indication = signalization: optical + acoustic = power source: from power source = frequency range: 0-60 Hz = packaging: 1 pc, blister




M0010 1/5/-/10
22 01 006 000 Z10

DC voltage: 12-690 V = AC voltage: 12-690 V = AC/DC voltage: 12 V, 24 V, 50 V, 120 V, 230 V, 400 V, 690 V = polarity indication = phase indication = signalization: optical + acoustic = power source: 9 V (included) = frequency range: 0-60 Hz = measuring of connections of circuits = packaging: 1 pc, blister



M0012 1/5/-/15
22 01 011 000 SN-02

detection: AC wiring = signalization: optical + acoustic = AC voltage: 70-1 000 V = dimensions: 153 x 22 mm = power source: 2x 1.5 V AAA (included) = packaging: 1 pc, blister



M0007A 1/-/30/60
22 05 000 010 GK7