



DC voltage: 0 to 250 V contactless • AC voltage: 70 to 250 V contactless • AC/DC voltage: 0–250 V, 70–250 V • polarity indication • non-contact measuring: polarity of sources and short-circuit, microwave ovens monitors emission • signalization: optical • power source: 2× 1.5 V LR41 (included) • frequency range: 0–60 Hz • packaging: 1 pc, blister



M0018
22 01 001 000

1/5/-/45
VT-110


DC voltage: 0 to 250 V contactless • AC voltage: 70 to 250 V contactless • AC/DC voltage: 0–250 V, 70–250 V • polarity indication • non-contact measuring: polarity of sources and short-circuit, microwave ovens monitors emission • two settings of sensitivity • signalization: optical + acoustic • power source: 2× 1.5 V LR44 (included) • frequency range: 0–60 Hz • packaging: 1 pc, blister



M0048
22 01 002 000

1/5/-/50
MS-48A


DC voltage: 6–690 V • AC voltage: 6–690 V • AC/DC voltage: 6 V, 12 V, 24 V, 50 V, 120 V, 230 V, 400 V, 690 V • polarity indication • phase indication • signalization: optical + acoustic • power source: 2× 1.5 V AAA (included) • frequency range: 45–65 Hz • measuring of connections of circuits • packaging: 1 pc, blister



M0071
22 01 013 000

1/-/-/10
VT-710

DC voltage: 12–690 V • AC voltage: 12–690 V • AC/DC voltage: 12 V, 24 V, 50 V, 120 V, 230 V, 400 V, 690 V • polarity indication • phase indication • signalization: optical + acoustic • power source: 9 V (included) • frequency range: 0–60 Hz • measuring of connections of circuits • packaging: 1 pc, blister



M0012A
22 01 014 000

1/5/-/15
VT-320

designed for battery type: AAA, AA, C, D, 9 V and for button cells 1.5 V • type: UNI D3 • value of load resistance for the AA, AAA, C, D, 9 V: universal • the value of load resistance for button batteries: universal • dimensions: 110 × 60 × 25 mm



N0322
22 03 003 000

1/-/5/50
UNI D3