


AC voltage: 2–600 V • AC current: 2–600 A • DC voltage: 200 mV – 600 V • clamp multimeter • screen display:
 3.5 digit • range selection: automatic • electrical resistance: 200 Ohm – 20 MOhm • circuit continuity • diode test • Data hold mode • auto power off • included: battery, manual, measurement tips • power source: 2× 3 V CR2032 (included) • dimensions: 36 × 76 × 190 mm



M0305 1/-/12/24
22 02 015 000 MD-310C

cable length: 95 cm • maximum load: 10 A, 1 kV, CAT III • colour: red, black • packaging: packet



S4003 1/-/-/200
23 04 000 300 BB58

cable length: 95 cm • maximum load: 2 A, 800 V, CAT III • possibility to tips exchange • colour: red, black • packaging: 1 pc, blister



S4001 1/5/-/50
23 04 000 100 L4126

Testers

- voltage tester for measuring voltage value
- also identifies phases, sequence and polarity
- detects DC and AC voltage, contact or non-contact
- results indicated optically and acoustically

DC voltage: 110–400 V • AC voltage: 110–400 V • AC/DC voltage: 110 V, 230 V, 400 V • polarity indication • phase indication • signalization: optical • power source: from power source • frequency range: 0–60 Hz • packaging: 1 pc, blister



M0014A 1/5/-/15
22 01 012 000 EM-4