

Blocuri de distributie OJL 135A

MOREK
Creating a better future For You

NEU



- Sectiune 2,5 ÷ 35 mm²
- 2 intrari, 6 iesiri
- 135 A, 1000 V
- Bimetal (Al/Cu)
- Clasa A, UL 94 V-0



| Tip | OJL 135 A gri | OJL 135 A albastru | OJL 135 A verde |
|--|-------------------|---|-------------------|
| Codul de comanda | MAB1135S10 | MAB1135B10 | MAB1135G10 |
| Design de culoare | Negru / Gri | Negru / Albastru | Negru / Verde |
| Sectiune conductor intrare Cu, Al (mm ²) | | 1x 2,5 ÷ 10 1x 2,5 ÷ 35 | |
| Sectiune conductor iesire Cu (mm ²) | | 2x 2,5 ÷ 10 4x 2,5 ÷ 16 | |
| Tensiune nominala (V) | | 1000 | |
| Curent nominal (A) | | 135 (Cu) / 120 (Al) | |
| Latime / Inaltime / Lungime (mm) | | 24,3 / 49 / 90 | |
| Cuplu de strangere (Nm) | | 3 Nm (2,5 ÷ 16 mm ²) 6 Nm (25 ÷ 35 mm ²) | |
| Montare | | Sina DIN, surub | |
| Greutate (g) | | 75 | |
| Unitate de ambalare | | 20 | |