

# Blocuri de distributie OJL 135A

**MOREK**  
Creating a better future For You

**NEU**



- Sectiune 2,5 ÷ 35 mm<sup>2</sup>
- 2 intrari, 6 iesiri
- 135 A, 1000 V
- Bimetal (Al/Cu)
- Clasa A, UL 94 V-0



Tip	OJL 135 A gri	OJL 135 A albastru	OJL 135 A verde
<b>Codul de comanda</b>	<b>MAB1135S10</b>	<b>MAB1135B10</b>	<b>MAB1135G10</b>
Design de culoare	Negru / Gri	Negru / Albastru	Negru / Verde
Sectiune conductor intrare Cu, Al (mm <sup>2</sup> )		1x 2,5 ÷ 10 1x 2,5 ÷ 35	
Sectiune conductor iesire Cu (mm <sup>2</sup> )		2x 2,5 ÷ 10 4x 2,5 ÷ 16	
Tensiune nominala (V)		1000	
Curent nominal (A)		135 (Cu) / 120 (Al)	
Latime / Inaltime / Lungime (mm)		24,3 / 49 / 90	
Cuplu de strangere (Nm)		3 Nm (2,5 ÷ 16 mm <sup>2</sup> ) 6 Nm (25 ÷ 35 mm <sup>2</sup> )	
Montare		Sina DIN, surub	
Greutate (g)		75	
Unitate de ambalare		20	