


Lămpi de semnalizare (Ba9s)



TRACON		Um	IP65	
	NYGBV61	NYGBV61T		max. 400 V
	NYGBV64P	NYGBV64PT		max. 400 V
	NYGBV63Z	NYGBV63ZT		max. 400 V
	NYGBV65S	NYGBV65ST		max. 400 V
	NYGBV66K	NYGBV66KT		max. 400 V
	NYGBV73Z	NYGBV73ZT		230-240 V
	NYGBV74P	NYGBV74PT		230-240 V
	NYGBV75S	NYGBV75ST		230-240 V
	NYGBV43Z	NYGBV43ZT		230-240 V
	NYGBV44P	NYGBV44PT		230-240 V
	NYGBV45S	NYGBV45ST		230-240 V
	NYGBV53Z	NYGBV53ZT		400 V
	NYGBV54P	NYGBV54PT		400 V
	NYGBV55S	NYGBV55ST		400 V

NYGD-1GR

page
K/32


NYGD-1GR

page
K/32


Lămpile de semnalizare se livrează fără bec.

Becul se alege în funcție de tensiunea de lucru.


* Tensiunea de lucru a becurilor din lămpile de semnalizare cu rezistență este de 130 V, iar a lămpilor cu transformator este de 6V



Normale



Cu rezistență



Cu transformator




TÜV MEEI TEST DOCUMENTATION
V-15180

RELEVANT STANDARD
EN 62094



Contactoare



I/32