











P0127	1/5/-/15
19 21 010 700	SE0117

- length: 7 m
- number of sockets: 1× 2P + PE SCHUKO
- voltage/current: 250 V~/10 A max.
- maximum load: 2 300 W
- type of insulation: PVC
- conductor: H05VV-F3G 1 mm²
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging

P0120	1/5/-/10
19 21 011 000	SE0110

- length: 10 m
- number of sockets: 1× 2P + PE SCHUKO
- voltage/current: 250 V~/10 A max.
- maximum load: 2 300 W
- type of insulation: PVC
- conductor: H05VV-F3G 1 mm²
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging





P0125Z	1/5/-/20
19 21 010 502	HE0115 (SE0115)










- length: 5 m
- number of sockets: 1× 2P + PE SCHUKO
- voltage/current: 250 V~/10 A max.
- maximum load: 2 300 W
- type of insulation: PVC
- conductor: H05VV-F3G 1 mm²
- material of the sockets + plugs: plastic /
- packaging: 1 pc, hanging

P01215	1/-/-/12
19 21 011 500	DG-YD01 (YC-DAX-2)





- length: 15 m
- number of sockets: 1× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 2 300 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.0 mm²
- material of the sockets + plugs: plastic
- packaging: 1 pc, foil

P01220	1/-/-/6
19 21 012 000	DG-YD01





- length: 20 m
- number of sockets: 1× 2P + PE SCHUKO
- voltage/current: 250 V~/10 A max.
- maximum load: 2 300 W
- type of insulation: PVC
- conductor: H05VV-F3G 1 mm²
- material of the sockets + plugs: plastic
- packaging: 1 pc, foil

P01230	1/-/-/4
19 21 013 000	DG-YD01 (P01230D)

- length: 30 m
- number of sockets: 1× 2P + PE SCHUKO
- voltage/current: 250 V~/10 A max.
- maximum load: 2 300 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.0 mm²
- material of the sockets + plugs: plastic
- packaging: 1 pc, foil

P01240	1/-/-/4
19 21 014 000	DG-YD01

- length: 40 m
- number of sockets: 1× 2P + PE SCHUKO
- voltage/current: 250 V~/10 A max.
- maximum load: 2 300 W
- type of insulation: PVC
- conductor: H05VV-F3G 1 mm²
- material of the sockets + plugs: plastic
- packaging: 1 pc, foil