

P01230R

1/-/-/4

19 21 013 001

P01230R



- length: 30 m
- conductor cross section: 1.5 mm²
- voltage: 230 V
- current: 16 A
- IP rating: IP20
- number of sockets: 1
- thermal fuse: no
- conductor: H05VV-F3G
- children protection
- packaging: 1 pc, shrink

1-phase 10A with PVC insulation

- extension cable with one socket, length: 3–30 m
- PVC insulation – ideal for the interior
- conductor: 1 mm², round socket, child socket covers
- in white, dark green or orange colour

P0123

1/-/-/25

19 21 010 300

SE0113



- length: 3 m
- number of sockets: 1× 2P + PE SCHUKO
- voltage/current: 250 V~/10 A max.
- maximum load: 2 300 W
- type of insulation: PVC
- conductor: H05VV-F3G 1 mm²
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging

P0125

1/5/-/20

19 21 010 500

SE0115



- length: 5 m
- number of sockets: 1× 2P + PE SCHUKO
- voltage/current: 250 V~/10 A max.
- maximum load: 2 300 W
- type of insulation: PVC
- conductor: H05VV-F3G 1 mm²
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging

P0127

1/5/-/15

19 21 010 700

SE0117



- length: 7 m
- number of sockets: 1× 2P + PE SCHUKO
- voltage/current: 250 V~/10 A max.
- maximum load: 2 300 W
- type of insulation: PVC
- conductor: H05VV-F3G 1 mm²
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging

P0120N

1/-/-/10

19 21 011 004

P0120N (P0120)



- length: 10 m
- number of sockets: 1× 2P + PE SCHUKO
- voltage/current: 250 V~/10 A max.
- maximum load: 2 300 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.0 mm²
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging

P01220

1/-/-/6

19 21 012 000

DG-YD01



- length: 20 m
- conductor cross section: 1.0 mm²
- voltage: 230 V
- current: 10 A
- IP rating: IP20
- number of sockets: 1
- thermal fuse: no
- conductor: H05VV-F3G
- max. unreel load: 10 A max./2 300 W
- children protection
- packaging: 1 pc, shrink

P01230

1/-/-/4

19 21 013 000

DG-YD01
(P01230D)

- length: 30 m
- conductor cross section: 1.0 mm²
- voltage: 230 V
- current: 10 A
- IP rating: IP20
- number of sockets: 1
- thermal fuse: no
- conductor: H05VV-F3G
- max. unreel load: 10 A max./2 300 W
- children protection
- packaging: 1 pc, shrink