

1-phase 16A with PVC insulation

- 15–30 m extension cable with one socket
- conductor cross-section: 1.5 mm², max. load: 3 680 W
- PVC insulation – ideal for the garage or workshop
- orange reflective colour – always visible to avoid tripping
- round socket, child socket covers

P0123R	1/5/-/25	
19 21 010 302	SE0113-1,5	
	 	
▪ length: 3 m ▪ number of sockets: 1× 2P + PE SCHUKO ▪ voltage/current: 250 V~/16 A max. ▪ maximum load: 3 680 W ▪ type of insulation: PVC ▪ conductor: H05VV-F3G 1.5 mm²		
▪ material of the sockets + plugs: plastic ▪ packaging: 1 pc, hanging		

P0125R	1/5/-/20	
19 21 010 503	SE0115-1,5	
	 	
▪ length: 5 m ▪ number of sockets: 1× 2P + PE SCHUKO ▪ voltage/current: 250 V~/16 A max. ▪ maximum load: 3 680 W ▪ type of insulation: PVC ▪ conductor: H05VV-F3G 1.5 mm²		
▪ material of the sockets + plugs: plastic ▪ packaging: 1 pc, hanging		

P0127R	1/-/-/20	
19 21 010 701	SE0117-1,5	
	 	
▪ length: 7 m ▪ number of sockets: 1× 2P + PE SCHUKO ▪ voltage/current: 250 V~/16 A max. ▪ maximum load: 3 680 W ▪ type of insulation: PVC ▪ conductor: H05VV-F3G 1.5 mm²		
▪ material of the sockets + plugs: plastic ▪ packaging: 1 pc, foil+hanging		

P0120R	1/-/-/10	
19 21 011 002	SE0110-1,5	
	 	
▪ length: 10 m ▪ number of sockets: 1× 2P + PE SCHUKO ▪ voltage/current: 250 V~/16 A max. ▪ maximum load: 3 680 W ▪ type of insulation: PVC ▪ conductor: H05VV-F3G 1.5 mm²		
▪ material of the sockets + plugs: plastic ▪ packaging: 1 pc, hanging		

P0122	1/5/-/20	
19 21 010 202	SE0112	
	 	
▪ length: 2 m ▪ number of sockets: 1× 2P + PE SCHUKO ▪ voltage/current: 250 V~/16 A max. ▪ maximum load: 3 680 W ▪ type of insulation: PVC ▪ conductor: H05VV-F3G 1.0 mm²		
▪ material of the sockets + plugs: plastic ▪ packaging: 1 pc, foil+hanging		

P01215R	1/-/-/6	
19 21 011 502	DG-YD01 (YC-DAX-2)	
	 	
▪ length: 15 m ▪ conductor cross section: 1.5 mm² ▪ voltage: 230 V ▪ current: 16 A ▪ IP rating: IP20 ▪ number of sockets: 1		
▪ thermal fuse: no ▪ conductor: H05VV-F3G ▪ max. unreeled load: 16 A max./3 680 W ▪ children protection ▪ packaging: 1 pc, shrink		

P01220R	1/-/-/6	
19 21 012 001	DG-YD01 (YC-DAX-2)	
	 	
▪ length: 20 m ▪ conductor cross section: 1.5 mm² ▪ voltage: 230 V ▪ current: 16 A ▪ IP rating: IP20 ▪ number of sockets: 1		
▪ thermal fuse: no ▪ conductor: H05VV-F3G ▪ max. unreeled load: 16 A max./3 680 W ▪ children protection ▪ packaging: 1 pc, shrink		

P01225R	1/-/-/4	
19 21 012 500	DG-YD01 (YC-DAX-2)	
	 	
▪ length: 25 m ▪ conductor cross section: 1.5 mm² ▪ voltage: 230 V ▪ current: 16 A ▪ IP rating: IP20 ▪ number of sockets: 1		
▪ thermal fuse: no ▪ conductor: H05VV-F3G ▪ max. unreeled load: 16 A max./3 680 W ▪ children protection ▪ packaging: 1 pc, shrink		