



<b>P14201</b>	1/-/-/6
19 22 341 000	E-K-4E
	 






- length: 10 m
- number of sockets: 4× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: rubber/neopren
- conductor: H07RN-F3G 1.5 mm<sup>2</sup>
- material of the sockets + plugs: plastic /
- packaging: 1 pc, foil

## Power supply extension cords and sockets SCHUKO

### Single socket extension cords SCHUKO




#### 1-phase with rubber insulation

- extension cable with 1 socket, length: 5–30 m
- neoprene or rubber insulation, IP44 enclosure
- conductor cross-section: 1.5 or 2.5 mm<sup>2</sup>, max. load: 3 680 W
- black colour, round socket with lid, child socket covers

<b>P01805</b>	1/-/-/20
19 21 010 504	E-008
	 






- length: 5 m
- number of sockets: 1× 2P + PE, IP44 SC
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: rubber/neopren
- conductor: H07RN-F3G 1.5 mm<sup>2</sup>
- material of the sockets + plugs: plastic /
- packaging: 1 pc, foil

<b>P01810</b>	1/-/-/6
19 21 031 000	E-008
	 






- length: 10 m
- number of sockets: 1× 2P + PE, IP44 SC
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: rubber/neopren
- conductor: H07RN-F3G 1.5 mm<sup>2</sup>
- material of the sockets + plugs: plastic /
- packaging: 1 pc, PE packet

<b>P01820</b>	1/-/-/2
19 21 032 000	E-008
	 



- length: 20 m
- number of sockets: 1× 2P + PE, IP44 SC
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: rubber/neopren
- conductor: H07RN-F3G 1.5 mm<sup>2</sup>
- material of the sockets + plugs: plastic /
- packaging: 1 pc, PE packet

<b>P01830</b>	1/-/-/2
19 21 033 000	E-008
	 



- length: 30 m
- number of sockets: 1× 2P + PE, IP44 SC
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: rubber/neopren
- conductor: H07RN-F3G 1.5 mm<sup>2</sup>
- material of the sockets + plugs: plastic /
- packaging: 1 pc, PE packet