











P1625R 1/5/-/10
19 22 160 502
SE1615-1,5
(SEH1615-1.5)

- length: 5 m
- number of sockets: 6× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.5 mm²
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging

P04219GU 1/-/3/12
19 22 040 191
P04219U










- length: 1.9 m
- number of sockets: 4× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.5 mm²
- material of the sockets + plugs: PC
- packaging: 1 pc, box

1-phase 1.0 mm² with PVC insulation





- extension cables with PVC insulation are ideal for household
- various lengths, conductor: 1 mm², max. load: 2 300 W
- round sockets with child socket covers, with/without switch
- in white, black or dark green – blend into any interior

P0321 1/5/-/35
19 22 030 150
SE0311





- length: 1.5 m
- number of sockets: 3× 2P + PE SCHUKO
- voltage/current: 250 V~/10 A max.
- maximum load: 2 300 W
- type of insulation: PVC
- conductor: H05VV-F3G 1 mm²
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging

P0322 1/5/15/30
19 22 030 200
SE0312





- length: 2 m
- number of sockets: 3× 2P + PE SCHUKO
- voltage/current: 250 V~/10 A max.
- maximum load: 2 300 W
- type of insulation: PVC
- conductor: H05VV-F3G 1 mm²
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging

P0323 1/5/-/20
19 22 030 300
SE0313





- length: 3 m
- number of sockets: 3× 2P + PE SCHUKO
- voltage/current: 250 V~/10 A max.
- maximum load: 2 300 W
- type of insulation: PVC
- conductor: H05VV-F3G 1 mm²
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging

P0325 1/5/-/20
19 22 030 500
SE0315





- length: 5 m
- number of sockets: 3× 2P + PE SCHUKO
- voltage/current: 250 V~/10 A max.
- maximum load: 2 300 W
- type of insulation: PVC
- conductor: H05VV-F3G 1 mm²
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging

P0421 1/5/-/20
19 22 040 150
SE0411

- length: 1.5 m
- number of sockets: 4× 2P + PE SCHUKO
- voltage/current: 250 V~/10 A max.
- maximum load: 2 300 W
- type of insulation: PVC
- conductor: H05VV-F3G 1 mm²
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging

P0423 1/5/-/20
19 22 040 300
SE0413

- length: 3 m
- number of sockets: 4× 2P + PE SCHUKO
- voltage/current: 250 V~/10 A max.
- maximum load: 2 300 W
- type of insulation: PVC
- conductor: H05VV-F3G 1 mm²
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging