













Power supply extension cords and sockets SCHUKO

Power supply extension cords SCHUKO

1-phase 1.5 mm² with PVC insulation

- extension cables with PVC insulation are ideal for household
- various lengths, conductor: 1.5 mm², max. load: 3 680 W
- round sockets with child socket covers, with/without switch
- in white – to blend discreetly into the interior

<p>P0321R</p> <p>19 22 030 153</p>  <p>8 592920 052662</p>	<p>1/5/-/20</p> <p>SE0311-1,5</p> 	<p>P0323R</p> <p>19 22 030 308</p>  <p>8 592920 016336</p>	<p>1/5/-/20</p> <p>SE0313-1,5</p> 
<p>↔</p> <p>1.5 m</p> <p>H05VV-F3G 1,5 mm²</p>	<ul style="list-style-type: none"> ▪ length: 1.5 m ▪ number of sockets: 3× 2P + PE SCHUKO ▪ voltage/current: 250 V~/16 A max. ▪ maximum load: max. 16 A ▪ type of insulation: PVC ▪ conductor: H05VV-F3G 1.5 mm² 	<p>↔</p> <p>3 m</p> <p>H05VV-F3G 1,5 mm²</p>	<ul style="list-style-type: none"> ▪ length: 3 m ▪ number of sockets: 3× 2P + PE SCHUKO ▪ voltage/current: 250 V~/16 A max. ▪ maximum load: 3 680 W ▪ type of insulation: PVC ▪ conductor: H05VV-F3G 1.5 mm²
<p>P0325R</p> <p>19 22 030 508</p>  <p>8 592920 016343</p>	<p>1/5/-/15</p> <p>SE0315-1,5</p> 	<p>P0421R</p> <p>19 22 040 152</p>  <p>8 592920 052679</p>	<p>1/5/-/20</p> <p>SE0411-1,5</p> 
<p>↔</p> <p>5 m</p> <p>H05VV-F3G 1,5 mm²</p>	<ul style="list-style-type: none"> ▪ length: 5 m ▪ number of sockets: 3× 2P + PE SCHUKO ▪ voltage/current: 250 V~/16 A max. ▪ maximum load: 3 680 W ▪ type of insulation: PVC ▪ conductor: H05VV-F3G 1.5 mm² 	<p>↔</p> <p>1.5 m</p> <p>H05VV-F3G 1,5 mm²</p>	<ul style="list-style-type: none"> ▪ length: 1.5 m ▪ number of sockets: 4× 2P + PE SCHUKO ▪ voltage/current: 250 V~/16 A max. ▪ maximum load: max. 16 A ▪ type of insulation: PVC ▪ conductor: H05VV-F3G 1.5 mm²
<p>P0423R</p> <p>19 22 040 302</p>  <p>8 592920 052747</p>	<p>1/5/-/20</p> <p>SE0413-1,5</p> 	<p>P0425R</p> <p>19 22 040 502</p>  <p>8 592920 064429</p>	<p>1/5/-/15</p> <p>SE0415-1,5 (SEH0415-1.5)</p> 
<p>↔</p> <p>3 m</p> <p>H05VV-F3G 1,5 mm²</p>	<ul style="list-style-type: none"> ▪ length: 3 m ▪ number of sockets: 4× 2P + PE SCHUKO ▪ voltage/current: 250 V~/16 A max. ▪ maximum load: max. 16 A ▪ type of insulation: PVC ▪ conductor: H05VV-F3G 1.5 mm² 	<p>↔</p> <p>5 m</p> <p>H05VV-F3G 1,5 mm²</p>	<ul style="list-style-type: none"> ▪ length: 5 m ▪ number of sockets: 4× 2P + PE SCHUKO ▪ voltage/current: 250 V~/16 A max. ▪ maximum load: 3 680 W ▪ type of insulation: PVC ▪ conductor: H05VV-F3G 1.5 mm²