







**P0525R** 1/-/-10  
19 22 050 508  
SE0515-1,5  
(SEH0515-1.5)




- length: 5 m
- number of sockets: 5× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.5 mm<sup>2</sup>
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging

**P0623R** 1/-/-10  
19 22 060 302  
SE0613-1,5




- length: 3 m
- number of sockets: 6× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.5 mm<sup>2</sup>
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging

**P0625R** 1/-/-10  
19 22 060 502  
SE0615-1,5




- length: 5 m
- number of sockets: 6× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.5 mm<sup>2</sup>
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging

**P1321R** 1/-/-15  
19 22 130 156  
SE1311-1,5




- length: 1.5 m
- number of sockets: 3× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.5 mm<sup>2</sup>
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging

**P1323R** 1/5/-20  
19 22 130 308  
SE1313-1,5  
(SEH1313-1.5)




- length: 3 m
- number of sockets: 3× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.5 mm<sup>2</sup>
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging

**P1325R** 1/-/-10  
19 22 130 508  
SE1315-1,5  
(SEH1315-1.5)




- length: 5 m
- number of sockets: 3× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.5 mm<sup>2</sup>
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging

**P1421R** 1/-/-15  
19 22 140 152  
SE1411-1,5




- length: 1.5 m
- number of sockets: 4× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.5 mm<sup>2</sup>
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging

**P1423R** 1/-/-10  
19 22 140 303  
SE1413-1,5  
(SEH1413-1.5)




- length: 3 m
- number of sockets: 4× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.5 mm<sup>2</sup>
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging

**P1425R** 1/5/-15  
19 22 140 503  
SE1415-1,5  
(SEH1415-1.5)

- length: 5 m
- number of sockets: 4× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.5 mm<sup>2</sup>
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging

**P1521R** 1/-/-15  
19 22 150 154  
SE1511-1,5

- length: 1.5 m
- number of sockets: 5× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.5 mm<sup>2</sup>
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging