

- length: 50 m
- number of sockets: 4× 2P + PE SCHUKO
- thermal fuse
- IP rating: IP44
- conductor: H07RN-F
- conductor cross section: 2.5 mm²
- reeled load 230 V~: 6.52 A max./1 500 W
- unreeled load 230 V~: 15.22 A max./3 500 W
- packaging: 1 pc

**P19220**

1/-/-/1

19 28 545 001

E-017

- length: 50 m
- number of sockets: 4× 2P + PE SCHUKO
- thermal fuse
- IP rating: IP44
- conductor: H05RR-F
- conductor cross section: 2.5 mm²
- reeled load 230 V~: 6.52 A max./1 500 W
- unreeled load 230 V~: 15.22 A max./3 500 W
- packaging: 1 pc

**P19221**

1/-/-/1

19 28 545 011

E-017

- length: 15 m
- number of sockets: 4× 2P + PE SCHUKO
- thermal fuse
- IP rating: IP44
- conductor: H07RN-F
- conductor cross section: 1.5 mm²
- reeled load 230 V~: 4.35 A max./1 000 W
- unreeled load 230 V~: 13.04 A max./3 000 W
- other functions: LED reflect. 20 W/1 600 lm/6 500 K

▪ packaging: 1 pc

**P08215**

1/-/-/1

19 28 441 500

P08215

1-phase PVC

- 1phase extension cable on reel with PVC insulation
- EMOS extension cable with thermal cutoff
- stable stand, reel and rubber-coated grip
- some also with backlit switch and guide loop (for reeling)

- length: 25 m
- number of sockets: 4× 2P + PE SCHUKO
- thermal fuse
- IP rating: IP20
- conductor: H05VV-F3G
- conductor cross section: 1.5 mm²
- reeled load 230 V~: 4.35 A max./1 000 W
- unreeled load 230 V~: 13 A max./3 000 W
- packaging: 1 pc

**P19427**

1/-/-/1

19 28 042 507

HJR-4BA