



- number of sockets: 4× 2P + PE SCHUKO
- voltage: 230 V~
- thermal fuse
- IP rating: IP44
- conductor: H07RN-F
- conductor cross section: 2.5 mm²
- reeled load 230 V: 6.52 A max./1 500 W
- unreeled load 230 V: 15.22 A max./3 500 W
- packaging: 1 pc



P19220
19 28 545 001

1/-/-1
E-017

- number of sockets: 4× 2P + PE SCHUKO
- voltage: 230 V~
- thermal fuse
- IP rating: IP44
- conductor: H05RR-F
- conductor cross section: 2.5 mm²
- reeled load 230 V: 6.52 A max./1 500 W
- unreeled load 230 V: 15.22 A max./3 500 W
- packaging: 1 pc



P19221
19 28 545 011


1/-/-1
E-017

1-phase PVC

- 1phase extension cable on reel with PVC insulation
- EMOS extension cable with thermal cutoff
- stable stand, reel and rubber-coated grip
- some also with backlit switch and guide loop (for reeling)

- number of sockets: 4× 2P + PE SCHUKO
- voltage: 230 V~
- fixed center
- thermal fuse
- IP rating: IP20
- conductor: H05VV-F3G
- conductor cross section: 1.5 mm²
- reeled load 230 V: 4.35 A max./1 000 W
- unreeled load 230 V: 13 A max./3 000 W

▪ packaging: 1 pc



P19427
19 28 042 507

1/-/-1
HJR-4BA

- number of sockets: 4× 2P + PE SCHUKO
- voltage: 230 V~
- thermal fuse
- switch
- IP rating: IP20
- conductor: H05VV-F3G
- conductor cross section: 1.5 mm²
- reeled load 230 V: 4.8 A max./1 100 W
- unreeled load 230 V: 16 A max./3 680 W

▪ packaging: 1 pc



P092251
19 28 042 504

1/-/-1
P092251