


- number of sockets: 4× 2P + PE SCHUKO = packaging: 1 pc
- voltage: 230 V~
- thermal fuse
- switch
- IP rating: IP20
- conductor: H05VV-F3G
- conductor cross section: 1.5 mm²
- reeled load 230 V: 4.8 A max./1 100 W
- unreeled load 230 V: 16 A max./3 680 W




P092501

1/-/-/1

19 28 045 003

P092501

- number of sockets: 4× 2P + PE SCHUKO
- voltage: 230 V~
- thermal fuse
- IP rating: IP20
- conductor: H05VV-F3G
- conductor cross section: 2.5 mm²
- reeled load 230 V: 6 A max./1 600 W
- unreeled load 230 V: 16 A max./3 600 W
- packaging: 1 pc



P09225M

1/-/-/1

19 28 042 501

E-4

- number of sockets: 4× 2P + PE SCHUKO
- voltage: 230 V~
- thermal fuse
- IP rating: IP20
- conductor: H05VV-F3G
- conductor cross section: 2.5 mm²
- reeled load 230 V: 6 A max. / 1 380 W
- unreeled load 230 V: 16 A max./3 600 W
- packaging: 1 pc



P09240M

1/-/-/1

19 28 044 001

E-4

- number of sockets: 4× 2P + PE SCHUKO
- voltage: 230 V~
- thermal fuse
- IP rating: IP20
- conductor: H05VV-F3G
- conductor cross section: 1.5 mm²
- reeled load 230 V: 4.8 A max./1 100 W
- unreeled load 230 V: 16 A max./3 680 W
- packaging: 1 pc




P09225

1/-/-/1

19 28 042 500

DG-4ZR-DB04
(HJR-4A)

- number of sockets: 4× 2P + PE SCHUKO
- voltage: 230 V~
- thermal fuse
- IP rating: IP20
- conductor: H05VV-F
- conductor cross section: 1.5 mm²
- reeled load 230 V: 4.8 A max./1 100 W
- unreeled load 230 V: 16 A max./3 680 W
- packaging: 1 pc



P09240

1/-/-/1

19 28 044 000

E-4