









P0425 1/5/-/15
19 22 040 500 SE0415





- length: 5 m
- number of sockets: 4× 2P + PE SCHUKO
- voltage/current: 250 V~/10 A max.
- maximum load: 2 300 W
- type of insulation: PVC
- conductor: H05VV-F3G 1 mm²
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging

P0521 1/5/-/15
19 22 050 150 SE0511





- length: 1.5 m
- number of sockets: 5× 2P + PE SCHUKO
- voltage/current: 250 V~/10 A max.
- maximum load: 2 300 W
- type of insulation: PVC
- conductor: H05VV-F3G 1 mm²
- children protection
- packaging: 1 pc, hanging

P0523 1/5/-/10
19 22 050 300 SE0513





- length: 3 m
- number of sockets: 5× 2P + PE SCHUKO
- voltage/current: 250 V~/10 A max.
- maximum load: 2 300 W
- type of insulation: PVC
- conductor: H05VV-F3G 1 mm²
- children protection
- packaging: 1 pc, hanging

P0525 1/5/-/15
19 22 050 500 SE0515





- length: 5 m
- number of sockets: 5× 2P + PE SCHUKO
- voltage/current: 250 V~/10 A max.
- maximum load: 2 300 W
- type of insulation: PVC
- conductor: H05VV-F3G 1 mm²
- children protection
- packaging: 1 pc, hanging

P0622 1/5/-/10
19 22 060 200 SE0612





- length: 2 m
- number of sockets: 6× 2P + PE SCHUKO
- voltage/current: 230 V~/10 A max.
- maximum load: 2 300 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.0 mm²
- material of the sockets + plugs: plastic
- packaging: 1 pc, PVC packet

P0623 1/5/-/10
19 22 060 300 SE0613





- length: 3 m
- number of sockets: 6× 2P + PE SCHUKO
- voltage/current: 230 V~/10 A max.
- maximum load: 2 300 W
- type of insulation: PVC
- conductor: H05VV-F3G 1 mm²
- material of the sockets + plugs: plastic
- packaging: 1 pc, PVC packet

P0625 1/10/10/20
19 22 060 500 SE0615





- length: 5 m
- number of sockets: 6× 2P + PE SCHUKO
- voltage/current: 230 V~/10 A max.
- maximum load: 2 300 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.0 mm²
- material of the sockets + plugs: plastic
- packaging: 1 pc, PVC packet

P1321 1/5/-/35
19 22 130 150 SE1311





- length: 1.5 m
- number of sockets: 3× 2P + PE SCHUKO
- voltage/current: 250 V~/10 A max.
- maximum load: 2 300 W
- type of insulation: PVC
- conductor: H05VV-F3G 1 mm²
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging

P1322 1/5/-/25
19 22 130 200 SE1312

- length: 2 m
- number of sockets: 3× 2P + PE SCHUKO
- voltage/current: 250 V~/10 A max.
- maximum load: 2 300 W
- type of insulation: PVC
- conductor: H05VV-F3G 1 mm²
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging

P1323 1/5/-/20
19 22 130 300 SE1313

- length: 3 m
- number of sockets: 3× 2P + PE SCHUKO
- voltage/current: 250 V~/10 A max.
- maximum load: 2 300 W
- type of insulation: PVC
- conductor: H05VV-F3G 1 mm²
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging