








**P0521R** 1/5/-/15  
19 22 050 153 SE0511-1,5

- length: 1.5 m
- number of sockets: 5× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: max. 16 A
- type of insulation: PVC
- conductor: H05VV-F3G 1.5 mm<sup>2</sup>
- material of the sockets + plugs: plastic
- packaging: 1 pc, foil+hanging





**P0523R** 1/-/-/16  
19 22 050 308 SE0513-1,5







- length: 3 m
- number of sockets: 5× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.5 mm<sup>2</sup>
- children protection
- packaging: 1 pc, hanging

**P0525R** 1/-/-/10  
19 22 050 508 SE0515-1,5 (SEH0515-1.5)





- length: 5 m
- number of sockets: 5× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.5 mm<sup>2</sup>
- children protection
- packaging: 1 pc, hanging

**P1323R** 1/5/-/20  
19 22 130 308 SE1313-1,5 (SEH1313-1.5)





- length: 3 m
- number of sockets: 3× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.5 mm<sup>2</sup>
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging

**P1325R** 1/-/-/10  
19 22 130 508 SE1315-1,5 (SEH1315-1.5)





- length: 5 m
- number of sockets: 3× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.5 mm<sup>2</sup>
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging

**P1423R** 1/-/-/10  
19 22 140 303 SE1413-1,5 (SEH1413-1.5)





- length: 3 m
- number of sockets: 4× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.5 mm<sup>2</sup>
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging

**P1425R** 1/5/-/15  
19 22 140 503 SE1415-1,5 (SEH1415-1.5)





- length: 5 m
- number of sockets: 4× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.5 mm<sup>2</sup>
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging

**P1523R** 1/-/-/10  
19 22 150 308 SE1513-1,5 (SEH1513-1.5)





- length: 3 m
- number of sockets: 5× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.5 mm<sup>2</sup>
- children protection
- packaging: 1 pc, hanging

**P1525R** 1/-/-/10  
19 22 150 508 SE1515-1,5 (SEH1515-1.5)

- length: 5 m
- number of sockets: 5× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.5 mm<sup>2</sup>
- children protection
- packaging: 1 pc, hanging

**P1623R** 1/5/-/10  
19 22 160 302 SE1613-1,5

- length: 3 m
- number of sockets: 6× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.5 mm<sup>2</sup>
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging