

P0525R 19 22 050 508	1/-/-/10 SE0515-1,5 (SEH0515-1.5) 		P0623R 19 22 060 302	1/-/-/10 SE0613-1,5 	
<ul style="list-style-type: none"> ▪ length: 5 m ▪ number of sockets: 5x 2P + PE SCHUKO ▪ voltage/current: 250 V~/16 A max. ▪ maximum load: 3 680 W ▪ type of insulation: PVC ▪ conductor: H05VV-F3G 1.5 mm² 	<ul style="list-style-type: none"> ▪ material of the sockets + plugs: plastic ▪ packaging: 1 pc, hanging 		<ul style="list-style-type: none"> ▪ length: 3 m ▪ number of sockets: 6x 2P + PE SCHUKO ▪ voltage/current: 250 V~/16 A max. ▪ maximum load: 3 680 W ▪ type of insulation: PVC ▪ conductor: H05VV-F3G 1.5 mm² 	<ul style="list-style-type: none"> ▪ material of the sockets + plugs: plastic ▪ packaging: 1 pc, hanging 	
P0625R 19 22 060 502	1/-/-/10 SE0615-1,5 		P1321R 19 22 130 156	1/-/-/15 SE1311-1,5 	
<ul style="list-style-type: none"> ▪ length: 5 m ▪ number of sockets: 6x 2P + PE SCHUKO ▪ voltage/current: 250 V~/16 A max. ▪ maximum load: 3 680 W ▪ type of insulation: PVC ▪ conductor: H05VV-F3G 1.5 mm² 	<ul style="list-style-type: none"> ▪ material of the sockets + plugs: plastic ▪ packaging: 1 pc, hanging 		<ul style="list-style-type: none"> ▪ length: 1.5 m ▪ number of sockets: 3x 2P + PE SCHUKO ▪ voltage/current: 250 V~/16 A max. ▪ maximum load: 3 680 W ▪ type of insulation: PVC ▪ conductor: H05VV-F3G 1.5 mm² 	<ul style="list-style-type: none"> ▪ material of the sockets + plugs: plastic ▪ packaging: 1 pc, hanging 	
P1323R 19 22 130 308	1/5/-/20 SE1313-1,5 (SEH1313-1.5) 		P1325R 19 22 130 508	1/-/-/10 SE1315-1,5 (SEH1315-1.5) 	
<ul style="list-style-type: none"> ▪ length: 3 m ▪ number of sockets: 3x 2P + PE SCHUKO ▪ voltage/current: 250 V~/16 A max. ▪ maximum load: 3 680 W ▪ type of insulation: PVC ▪ conductor: H05VV-F3G 1.5 mm² 	<ul style="list-style-type: none"> ▪ material of the sockets + plugs: plastic ▪ packaging: 1 pc, hanging 		<ul style="list-style-type: none"> ▪ length: 5 m ▪ number of sockets: 3x 2P + PE SCHUKO ▪ voltage/current: 250 V~/16 A max. ▪ maximum load: 3 680 W ▪ type of insulation: PVC ▪ conductor: H05VV-F3G 1.5 mm² 	<ul style="list-style-type: none"> ▪ material of the sockets + plugs: plastic ▪ packaging: 1 pc, hanging 	
P1421R 19 22 140 152	1/-/-/15 SE1411-1,5 		P1423R 19 22 140 303	1/-/-/10 SE1413-1,5 (SEH1413-1.5) 	
<ul style="list-style-type: none"> ▪ length: 1.5 m ▪ number of sockets: 4x 2P + PE SCHUKO ▪ voltage/current: 250 V~/16 A max. ▪ maximum load: 3 680 W ▪ type of insulation: PVC ▪ conductor: H05VV-F3G 1.5 mm² 	<ul style="list-style-type: none"> ▪ material of the sockets + plugs: plastic ▪ packaging: 1 pc, hanging 		<ul style="list-style-type: none"> ▪ length: 3 m ▪ number of sockets: 4x 2P + PE SCHUKO ▪ voltage/current: 250 V~/16 A max. ▪ maximum load: 3 680 W ▪ type of insulation: PVC ▪ conductor: H05VV-F3G 1.5 mm² 	<ul style="list-style-type: none"> ▪ material of the sockets + plugs: plastic ▪ packaging: 1 pc, hanging 	
P1425R 19 22 140 503	1/5/-/15 SE1415-1,5 (SEH1415-1.5) 		P1521R 19 22 150 154	1/-/-/15 SE1511-1,5 	
<ul style="list-style-type: none"> ▪ length: 5 m ▪ number of sockets: 4x 2P + PE SCHUKO ▪ voltage/current: 250 V~/16 A max. ▪ maximum load: 3 680 W ▪ type of insulation: PVC ▪ conductor: H05VV-F3G 1.5 mm² 	<ul style="list-style-type: none"> ▪ material of the sockets + plugs: plastic ▪ packaging: 1 pc, hanging 		<ul style="list-style-type: none"> ▪ length: 1.5 m ▪ number of sockets: 5x 2P + PE SCHUKO ▪ voltage/current: 250 V~/16 A max. ▪ maximum load: 3 680 W ▪ type of insulation: PVC ▪ conductor: H05VV-F3G 1.5 mm² 	<ul style="list-style-type: none"> ▪ material of the sockets + plugs: plastic ▪ packaging: 1 pc, hanging 	