











**PM1002** 1/-/-/6  
19 14 081 100 PM1002

- length: 10 m
- number of sockets: 1× connector 5P 32A
- voltage/current: 400 V~
- maximum load: max. 16 A
- type of insulation: rubber
- conductor: CGSG 5C × 2.5 H05RR-F

packaging: 1 pc, PP (PE) packet





**PM1003** 1/-/-/-  
19 14 081 150 PM1003

- length: 15 m
- number of sockets: 1× connector 5P 32A
- voltage/current: 400 V~
- maximum load: max. 16 A
- type of insulation: rubber
- conductor: CGSG 5C × 2.5 H05RR-F

packaging: 1 pc, PP (PE) packet





**PM1004** 1/-/-/-  
19 14 081 200 PM1004

- length: 20 m
- number of sockets: 1× connector 5P 32A
- voltage/current: 400 V~
- maximum load: max. 16 A
- type of insulation: rubber
- conductor: CGSG 5C × 2.5 H05RR-F

packaging: 1 pc, PP (PE) packet

**PM1005** 1/-/-/3  
19 14 086 250 PM1005

- length: 25 m
- number of sockets: 1× connector 5P 32A
- voltage/current: 400 V~
- maximum load: max. 16 A
- type of insulation: rubber
- conductor: CGSG 5C × 2.5 H05RR-F

packaging: 1 pc, PP (PE) packet


## Cable reels

## SCHUKO

### 3-phase rubber

- 3phase extension cable on reel with neoprene insulation
- immune to water (IP44), extreme temperatures and oils
- EMOS extension cable with thermal cutoff
- stable stand, reel and rubber-coated grip

- number of sockets: 1× CEE 3P + N + PE (16 A), 2× 2
  - voltage: 230 V~/400 V~
  - thermal fuse
  - IP rating: IP44
  - conductor: H07RN-F
  - conductor cross section: 1.5 mm<sup>2</sup>
  - reeled load 230 V: 4.35 A max./1 000 W
  - unreeled load 230 V: 13 A max./3 000 W
  - reeled load 400 V: 6.25 A max./2 500 W
- unreeled load 400 V: 12.5 A max./5 000 W  
packaging: 1 pc



**P192250** 1/-/-/1  
19 28 432 500 E-102A