



- number of sockets: 4× 2P + PE SCHUKO
- voltage: 230 V~
- thermal fuse
- IP rating: IP20
- conductor: H05VV-F3G
- conductor cross section: 1.5 mm<sup>2</sup>
- reeled load 230 V: 4.8 A max./1 100 W
- unreeled load 230 V: 16 A max./3 680 W
- packaging: 1 pc



**P09250** 1/-/-/1  
19 28 045 000 DG-4ZR-DB04  
(HJR-4)

- number of sockets: 4× 2P + PE SCHUKO
- voltage: 230 V~
- thermal fuse
- IP rating: IP20
- conductor: H05VV-F3G
- conductor cross section: 1.0 mm<sup>2</sup>
- reeled load 230 V: 4.8 A max./1 100 W
- unreeled load 230 V: 10 A max./2 300 W
- packaging: 1 pc



**P09220** 1/-/-/1  
19 28 142 000 DG-4ZR-DB04  
(HJR-4AC)

- number of sockets: 4× 2P + PE SCHUKO
- voltage: 230 V~
- thermal fuse
- IP rating: IP20
- conductor: H05VV-F3G
- conductor cross section: 1.0 mm<sup>2</sup>
- reeled load 230 V: 4 A max./920 W
- unreeled load 230 V: 10 A max./2 300 W
- packaging: 1 pc



**P19515** 1/-/-/2  
19 28 141 500 E-4ZR-15M-D04

- number of sockets: 4× 2P + PE SCHUKO
- voltage: 230 V~
- thermal fuse
- IP rating: IP20
- conductor: H05VV-F3G
- conductor cross section: 1.0 mm<sup>2</sup>
- reeled load 230 V~: 4 A max./920 W
- unreeled load 230 V~: 10 A max./2 300 W
- packaging: 1 pc



**P19510** 1/-/-/6  
19 28 141 000 E-XD04