

## Surge protectors EMOS SCHUKO

- extension cable with overvoltage protection
- protects TV, satellite or laptop from mains overvoltage
- black or white design, backlit switch & child socket covers

- rated voltage: 230 V~, 50 Hz
- maximum load: 3 680 W
- conductor: H05VV-F3G 1.5 mm<sup>2</sup>
- energy absorption: 900 J
- protection level Up: 1.7 kV (L/N-PE, L-N)
- open-circuit voltage UOC: 6 kV
- response time: <1 ns
- connection indicator
- surge protector indicator

- dimensions: 342 × 66 × 50 mm
- packaging: 1 pc, box



**P54212** 1/-/-/6  
19 09 040 202 G3040



- rated voltage: 230 V~, 50 Hz
- maximum load: 3 680 W
- conductor: H05VV-F3G 1.5 mm<sup>2</sup>
- energy absorption: 1 800 J
- protection level Up: 1.7 kV (L/N-PE, L-N)
- open-circuit voltage UOC: 6 kV
- response time: <1 ns
- antenna (coaxial protection): yes, IEC
- connection indicator

- surge protector indicator
- dimensions: 342 × 66 × 50 mm
- packaging: 1 pc, box



**P54222** 1/-/-/6  
19 09 040 203 G5142



- rated voltage: 230 V~, 50 Hz
- maximum load: 3 680 W
- conductor: H05VV-F3G 1.5 mm<sup>2</sup>
- energy absorption: 1 800 J
- protection level Up: 1.7 kV (L/N-PE, L-N)
- open-circuit voltage UOC: 6 kV
- response time: <1 ns
- tel./Fax/DSL protection: yes, TEL/FAX/DSL, RJ11/RJ
- antenna (coaxial protection): yes, IEC

- connection indicator
- surge protector indicator
- dimensions: 398 × 110 × 50 mm
- packaging: 1 pc, box



**P54252** 1/-/-/6  
19 09 480 301 G5183

