

type: digital = outdoor using = voltage/current: 230 V~/16 A max. = maximum load: 3 680 W = minimal time setting: 1 minute = option of manual switch-on = number of programs: 10 = number of switching per day: 10 = function to change summer/winter time = IP rating: IP44 = packaging: 1 pc, blister

**P5525**

1/-/12/24

19 27 110 020

TGE-5

type: digital = voltage/current: 230 V~/16 A max. = maximum load: 3 680 W = minimal time setting: 1 minute = option of manual switch-on = number of programs: 8 = number of switching per day: 8 = function to change summer/winter time = IP rating: IP20 = packaging: 1 pc, blister

**P5521**

1/2/8/24

19 27 110 010

TS-ED1

type: mechanical = voltage/current: 230 V~/16 A max. = maximum load: 3 680 W = minimal time setting: 15 minutes = option of manual switch-on = number of switching per day: 96 = IP rating: IP20 = packaging: 1 pc, blister

**P5522**

1/-/12/24

19 27 010 010

1E/2A

type: mechanical = voltage/current: 230 V~/16 A max. = maximum load: 3 680 W = minimal time setting: 30 minutes = option of manual switch-on = number of switching per day: 48 = IP rating: IP20 = packaging: 1 pc, blister

**P5523**

1/4/-/36

19 27 010 020

15GD/3A

type: mechanical = voltage/current: 230 V~/16 A max. = maximum load: 3 680 W = minimal time setting: 30 minutes = number of switching per day: 48 = IP rating: IP44 = packaging: 1 pc, blister

**P5526**

1/2/-/40

19 27 110 031

P5526