





H7001 1/-/-/60
30 70 000 001 H7001




8 595025 362483




input voltage: 100–240 V~ 50/60 Hz = protection against overload, overvoltage and short circuit = designed for: universal = LED indicators = output voltage: 12 V DC = output current: max. 3 000 mA = power supply type: connecting block = dimensions: 60 × 45 × 76 mm = packaging: 1 pc, box

H7006 1/-/-/40
30 70 000 006 H7006



8 592920 019573



input voltage: 100–240 V~ 50/60 Hz = designed for: RL EMOS source for videophones = output voltage: 12 V DC = output current: max. 2 000 mA = dimensions: 35 × 50 × 80 × mm = packaging: 1 pc, box

Wireless doorbells

Wireless doorbells

- EMOS doorbells have a battery- or mains-powered receiver
- paired from production/paired by user with ease in seconds
- new models with signal repeater – unlimited range
- with 1 or 2 waterproof buttons, more buttons can be added
- volume controls, optical signalisation, up to 52 ringtones

reach of the button: 120 m = number of melodies: 16 = pairing method: automatic pairing – self-learning = special functions: USB output – 2 A, repeater function – allows to extend the reach of the button by a few hundred meters = optical signaling on the doorbell = optical signaling on the button = maximum ringing volume: 85 dB = option to add another button: yes, max. 8 = number of buttons in a package: 1 pc = extra (spare) button: P5760T = waterproof button = power button: 1× 3 V CR2032 (included) = number of receivers in a package: 1 pc = volume control: yes, 5 levels = power supply of the main unit: 230 V DC



P5760 1/-/5/10
34 02 060 000 P5760

reach of the button: 120 m = number of melodies: 16 = pairing method: automatic pairing – self-learning = special functions: repeater function – allows extending the range of the button by several hundred meters. = optical signaling on the doorbell = optical signaling on the button = maximum ringing volume: 85 dB = option to add another button: yes, max. 8 = number of buttons in a package: 1 pc = extra (spare) button: P5760T = waterproof button = power button: 1× 3 V CR2032 (included) = number of receivers in a package: 1 pc = volume control: yes, 5 levels = power supply of the main unit: 3× 1.5 V AA (not included)



P5763 1/-/5/10
34 02 060 001 P5763