











P1523R 1/-/-/10
19 22 150 308
SE1513-1,5
(SEH1513-1.5)





- length: 3 m
- number of sockets: 5× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.5 mm²
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging

P1525R 1/-/-/10
19 22 150 508
SE1515-1,5
(SEH1515-1.5)





- length: 5 m
- number of sockets: 5× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.5 mm²
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging

P1621R 1/-/-/15
19 22 160 152
SE1611-1,5





- length: 1.5 m
- number of sockets: 6× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.5 mm²
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging

P1623R 1/-/-/10
19 22 160 302
SE1613-1,5





- length: 3 m
- number of sockets: 6× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.5 mm²
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging

P1625R 1/-/-/10
19 22 160 502
SE1615-1,5
(SEH1615-1.5)





- length: 5 m
- number of sockets: 6× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.5 mm²
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging

P1322RU 1/-/-/10
19 22 130 201
P1322RU

- length: 2 m
- number of sockets: 3× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.5 mm²
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging

P1523RU 1/-/-/10
19 22 150 304
P1523RU

- length: 3 m
- number of sockets: 5× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.5 mm²
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging

PC1321R 1/-/-/15
19 22 330 152
SE1311-1,5






- length: 1.5 m
- number of sockets: 3× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.5 mm²
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging





PC1421R 1/-/-/15
19 22 340 151
SE1411-1,5






- length: 1.5 m
- number of sockets: 4× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.5 mm²
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging

PC1423R 1/-/-/10
19 22 340 301
SE1413-1,5

- length: 3 m
- number of sockets: 4× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.5 mm²
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging