





PC1425R 1/-/-15
19 22 340 502 SE1415-1.5

- length: 5 m
- number of sockets: 4× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.5 mm²
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging

PC1521R 1/-/-15
19 22 350 151 SE1511-1.5






- length: 1.5 m
- number of sockets: 5× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.5 mm²
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging

PC1621R 1/-/-15
19 22 360 150 SE1611-1.5






- length: 1.5 m
- number of sockets: 6× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.5 mm²
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging

P0321 1/5/-/20
19 22 030 150 SE0311






- length: 1.5 m
- number of sockets: 3× 2P + PE SCHUKO
- voltage/current: 250 V~/10 A max.
- maximum load: 2 300 W
- type of insulation: PVC
- conductor: H05VV-F3G 1 mm²
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging





P0322 1/5/-/20
19 22 030 200 SE0312








- length: 2 m
- number of sockets: 3× 2P + PE SCHUKO
- voltage/current: 250 V~/10 A max.
- maximum load: 2 300 W
- type of insulation: PVC
- conductor: H05VV-F3G 1 mm²
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging

P0421 1/5/-/20
19 22 040 150 SE0411

- length: 1.5 m
- number of sockets: 4× 2P + PE SCHUKO
- voltage/current: 250 V~/10 A max.
- maximum load: 2 300 W
- type of insulation: PVC
- conductor: H05VV-F3G 1 mm²
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging





P0521 1/5/-/15
19 22 050 150 SE0511







- length: 1.5 m
- number of sockets: 5× 2P + PE SCHUKO
- voltage/current: 250 V~/10 A max.
- maximum load: 2 300 W
- type of insulation: PVC
- conductor: H05VV-F3G 1 mm²
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging

P0622 1/5/-/15
19 22 060 200 SE0612





- length: 2 m
- number of sockets: 6× 2P + PE SCHUKO
- voltage/current: 230 V~/10 A max.
- maximum load: 2 300 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.0 mm²
- material of the sockets + plugs: plastic
- packaging: 1 pc, PVC packet

P1321 1/5/-/20
19 22 130 150 SE1311

- length: 1.5 m
- number of sockets: 3× 2P + PE SCHUKO
- voltage/current: 250 V~/10 A max.
- maximum load: 2 300 W
- type of insulation: PVC
- conductor: H05VV-F3G 1 mm²
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging

P1322 1/5/-/20
19 22 130 200 SE1312

- length: 2 m
- number of sockets: 3× 2P + PE SCHUKO
- voltage/current: 250 V~/10 A max.
- maximum load: 2 300 W
- type of insulation: PVC
- conductor: H05VV-F3G 1 mm²
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging