









**P1523R** 1/-/-/10  
19 22 150 308  
SE1513-1,5  
(SEH1513-1.5)




- length: 3 m
- number of sockets: 5× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.5 mm<sup>2</sup>
- children protection
- packaging: 1 pc, hanging

**P1525R** 1/-/-/10  
19 22 150 508  
SE1515-1,5  
(SEH1515-1.5)




- length: 5 m
- number of sockets: 5× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.5 mm<sup>2</sup>
- children protection
- packaging: 1 pc, hanging

**P1621R** 1/-/-/15  
19 22 160 152  
SE1611-1,5




- length: 1.5 m
- number of sockets: 6× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.5 mm<sup>2</sup>
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging

**P1623R** 1/-/-/10  
19 22 160 302  
SE1613-1,5

- length: 3 m
- number of sockets: 6× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.5 mm<sup>2</sup>
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging

**P1625R** 1/-/-/10  
19 22 160 502  
SE1615-1,5  
(SEH1615-1.5)

- length: 5 m
- number of sockets: 6× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.5 mm<sup>2</sup>
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging




**PC1321R** 1/-/-/15  
19 22 330 152  
SE1311-1,5






- length: 1.5 m
- number of sockets: 3× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.5 mm<sup>2</sup>
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging


**PC1421R** 1/-/-/15  
19 22 340 151  
SE1411-1,5

- length: 1.5 m
- number of sockets: 4× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.5 mm<sup>2</sup>
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging




**PC1521R** 1/-/-/15  
19 22 350 151  
SE1511-1,5





- length: 1.5 m
- number of sockets: 5× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.5 mm<sup>2</sup>
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging

**PC1621R** 1/-/-/15  
19 22 360 150  
SE1611-1,5

- length: 1.5 m
- number of sockets: 6× 2P + PE SCHUKO
- voltage/current: 250 V~/16 A max.
- maximum load: 3 680 W
- type of insulation: PVC
- conductor: H05VV-F3G 1.5 mm<sup>2</sup>
- material of the sockets + plugs: plastic
- packaging: 1 pc, hanging