













# Assembled cords 3F program 400 V





## 3-phase rubber





- 380 V~ extension cable, length: 5–25 m
- rubber insulation, ideal for outdoor use, enclosure: IP44
- conductor cross-section: 2.5 mm<sup>2</sup>, max. load: 6 000 W
- black colour





<b>PM0901</b>	1/-/-	
19 14 071 050	PM0901	
		
8 595025 381071	5 m	2,5 mm <sup>2</sup>
▪ length: 5 m	▪ packaging: 1 pc, PP (PE) packet	
▪ number of sockets: 1× connector 5P 16A		
▪ voltage/current: 400 V~		
▪ maximum load: max. 16 A		
▪ type of insulation: rubber		
▪ conductor: CGSG 5C × 2.5 H05RR-F		

<b>PM0902</b>	1/-/-/6	
19 14 071 100	PM0902	
		
8 595025 381088	10 m	2,5 mm <sup>2</sup>
▪ length: 10 m	▪ packaging: 1 pc, PP (PE) packet	
▪ number of sockets: 1× connector 5P 16A		
▪ voltage/current: 400 V~		
▪ maximum load: max. 16 A		
▪ type of insulation: rubber		
▪ conductor: CGSG 5C × 2.5 H05RR-F		

<b>PM0903</b>	1/-/-	
19 14 071 150	PM0903	
		
8 595025 381095	15 m	2,5 mm <sup>2</sup>
▪ length: 15 m	▪ packaging: 1 pc, PP (PE) packet	
▪ number of sockets: 1× connector 5P 16A		
▪ voltage/current: 400 V~		
▪ maximum load: max. 16 A		
▪ type of insulation: rubber		
▪ conductor: CGSG 5C × 2.5 H05RR-F		

<b>PM0904</b>	1/-/-/3	
19 14 071 200	PM0904	
		
8 595025 381101	20 m	2,5 mm <sup>2</sup>
▪ length: 20 m	▪ packaging: 1 pc, PP (PE) packet	
▪ number of sockets: 1× connector 5P 16A		
▪ voltage/current: 400 V~		
▪ maximum load: max. 16 A		
▪ type of insulation: rubber		
▪ conductor: CGSG 5C × 2.5 H05RR-F		

<b>PM0905</b>	1/-/-	
19 14 071 250	PM0905	
		
8 595025 381118	25 m	2,5 mm <sup>2</sup>
▪ length: 25 m	▪ packaging: 1 pc, PP (PE) packet	
▪ number of sockets: 1× connector 5P 16A		
▪ voltage/current: 400 V~		
▪ maximum load: max. 16 A		
▪ type of insulation: rubber		
▪ conductor: CGSG 5C × 2.5 H05RR-F		

<b>PM1001</b>	1/-/-/8	
19 14 081 050	PM1001	
		
8 595025 381125	5 m	2,5 mm <sup>2</sup>
▪ length: 5 m	▪ packaging: 1 pc, PP (PE) packet	
▪ number of sockets: 1× connector 5P 32A		
▪ voltage/current: 400 V~		
▪ maximum load: max. 16 A		
▪ type of insulation: rubber		
▪ conductor: CGSG 5C × 2.5 H05RR-F		