













## Assembled cords





## 3-phase rubber





- 380 V~ extension cable, length: 5–25 m
- rubber insulation, ideal for outdoor use, enclosure: IP44
- conductor cross-section: 2.5 or 4.0 mm<sup>2</sup>
- max. load: 3 680 W or 22 000 W





<b>PM0902</b>	1/-/-6	
19 14 071 100	PM0902	
		
<ul style="list-style-type: none"> <li>▪ length: 10 m</li> <li>▪ conductor cross section: 2.5 mm<sup>2</sup></li> <li>▪ voltage: 400 V~</li> <li>▪ current: 16 A</li> <li>▪ IP rating: IP44</li> <li>▪ number of sockets: 1</li> </ul>	<ul style="list-style-type: none"> <li>▪ thermal fuse: no</li> <li>▪ conductor: CGSG 5C × H05RR-F</li> <li>▪ max. unreel load: 16 A max./3 680 W</li> <li>▪ children protection: no</li> <li>▪ packaging: 1 pc, packet</li> </ul>	

<b>PM0904</b>	1/-/-3	
19 14 071 200	PM0904	
		
<ul style="list-style-type: none"> <li>▪ length: 20 m</li> <li>▪ conductor cross section: 2.5 mm<sup>2</sup></li> <li>▪ voltage: 400 V~</li> <li>▪ current: 16 A</li> <li>▪ IP rating: IP44</li> <li>▪ number of sockets: 1</li> </ul>	<ul style="list-style-type: none"> <li>▪ thermal fuse: no</li> <li>▪ conductor: CGSG 5C × H05RR-F</li> <li>▪ max. unreel load: 16 A max./3 680 W</li> <li>▪ children protection: no</li> <li>▪ packaging: 1 pc, packet</li> </ul>	

<b>PM0905</b>	1/-/-2	
19 14 071 250	PM0905	
		
<ul style="list-style-type: none"> <li>▪ length: 25 m</li> <li>▪ conductor cross section: 2.5 mm<sup>2</sup></li> <li>▪ voltage: 400 V~</li> <li>▪ current: 16 A</li> <li>▪ IP rating: IP44</li> <li>▪ number of sockets: 1</li> </ul>	<ul style="list-style-type: none"> <li>▪ thermal fuse: no</li> <li>▪ conductor: CGSG 5C × H05RR-F</li> <li>▪ max. unreel load: 16 A max./3 680 W</li> <li>▪ children protection: no</li> <li>▪ packaging: 1 pc, packet</li> </ul>	

<b>PM1102</b>	1/-/-4	
19 14 081 102		
		
<ul style="list-style-type: none"> <li>▪ length: 10 m</li> <li>▪ conductor cross section: 4.0 mm<sup>2</sup></li> <li>▪ voltage: 400 V~</li> <li>▪ current: 32 A</li> <li>▪ IP rating: IP44</li> <li>▪ number of sockets: 1</li> </ul>	<ul style="list-style-type: none"> <li>▪ thermal fuse: no</li> <li>▪ conductor: CGSG 5C × H07RN-F</li> <li>▪ max. unreel load: 32 A max./22 000 W</li> <li>▪ children protection: no</li> <li>▪ packaging: 1 pc, packet</li> </ul>	

<b>PM1103</b>	1/-/-5	
19 14 081 103		
		
<ul style="list-style-type: none"> <li>▪ length: 15 m</li> <li>▪ conductor cross section: 4.0 mm<sup>2</sup></li> <li>▪ voltage: 400 V~</li> <li>▪ current: 32 A</li> <li>▪ IP rating: IP44</li> <li>▪ number of sockets: 1</li> </ul>	<ul style="list-style-type: none"> <li>▪ thermal fuse: no</li> <li>▪ conductor: CGSG 5C × H07RN-F</li> <li>▪ max. unreel load: 32 A max./22 000 W</li> <li>▪ children protection: no</li> <li>▪ packaging: 1 pc, packet</li> </ul>	

<b>PM1104</b>	1/-/-3	
19 14 081 104		
		
<ul style="list-style-type: none"> <li>▪ length: 20 m</li> <li>▪ conductor cross section: 4.0 mm<sup>2</sup></li> <li>▪ voltage: 400 V~</li> <li>▪ current: 32 A</li> <li>▪ IP rating: IP44</li> <li>▪ number of sockets: 1</li> </ul>	<ul style="list-style-type: none"> <li>▪ thermal fuse: no</li> <li>▪ conductor: CGSG 5C × H07RN-F</li> <li>▪ max. unreel load: 32 A max./22 000 W</li> <li>▪ children protection: no</li> <li>▪ packaging: 1 pc, packet</li> </ul>	