Assembled cords

3-phase rubber

- 380 V~ extension cable, length: 5–25 m
- rubber insulation, ideal for outdoor use, enclosure: IP44
- conductor cross-section: 2.5 or 4.0 mm²
- max. load: 3 680 W or 22 000 W

PM0902 1/-/-/6
19 14 071 100 PM0902

8 595025 381088 | 10 m | H05RR-F 2,5 mm²



- length: 10 m
- conductor cross section: 2.5 mm²
- voltage: 400 V~
- current: 16 A
- IP rating: IP44
- number of sockets: 1
- thermal fuse: no
- conductor: CGSG 5C × H05RR-F
- max. unreeled load: 16 A max./3 680 W
- children protection: no
- packaging: 1 pc, packet

PM0904 1/-/-/3
19 14 071 200 PM0904

8 595025 381101 | 20 m | H05RR-F 2,5 mm²



- length: 20 m
- conductor cross section: 2.5 mm²
- voltage: 400 V~
- current: 16 A
- IP rating: IP44
- number of sockets: 1
- thermal fuse: no
- conductor: CGSG 5C × H05RR-F
- max. unreeled load: 16 A max./3 680 W
- children protection: no
- packaging: 1 pc, packet

PM0905 1/-/-/2
19 14 071 250 PM0905

8 595025 381118 | 25 m | H05RR-F 2,5 mm²



- length: 25 m
- conductor cross section: 2.5 mm²
- voltage: 400 V~
- current: 16 A
- IP rating: IP44
- number of sockets: 1
- thermal fuse: no
- conductor: CGSG 5C × H05RR-F
- max. unreeled load: 16 A max./3 680 W
- children protection: no
- packaging: 1 pc, packet

PM1102 1/-/-/4
19 14 081 102

8 592920 110065 | 10 m | H07RN-F 4,0 mm²



- length: 10 m
- conductor cross section: 4,0 mm²
- voltage: 400 V~
- current: 32 A
- IP rating: IP44
- number of sockets: 1
- thermal fuse: no
- conductor: CGSG 5C × H07RN-F
- max. unreeled load: 32 A max./22 000 W
- children protection: no
- packaging: 1 pc, packet

PM1103 1/-/-/5
19 14 081 103

8 592920 110072 | 15 m | H07RN-F 4,0 mm²



- length: 15 m
- conductor cross section: 4,0 mm²
- voltage: 400 V~
- current: 32 A
- IP rating: IP44
- number of sockets: 1
- thermal fuse: no
- conductor: CGSG 5C × H07RN-F
- max. unreeled load: 32 A max./22 000 W
- children protection: no
- packaging: 1 pc, packet

PM1104 1/-/-/3
19 14 081 104

8 592920 110089 | 20 m | H07RN-F 4,0 mm²



- length: 20 m
- conductor cross section: 4,0 mm²
- voltage: 400 V~
- current: 32 A
- IP rating: IP44
- number of sockets: 1
- thermal fuse: no
- conductor: CGSG 5C × H07RN-F
- max. unreeled load: 32 A max./22 000 W
- children protection: no
- packaging: 1 pc, packet