EMOS www.emos.eu Order Code Item Number Packaging Type

PM1105 1/-/-/2

19 14 081 105



8 592920 110096

25 m

H07RN-F 4,0 mm²

- length: 25 m
- conductor cross section: 4,0 mm²
- voltage: 400 V~
- current: 32 A
- IP rating: IP44
- number of sockets: 1
- thermal fuse: no
- conductor: CGSG 5C × H07RN-F
- max. unreeled load: 32 A max./22 000 W
- children protection: no
- packaging: 1 pc, packet

Cable reels

SCHUKO

3-phase rubber

- 3phase extension cable on reel with neoprene insulation
- immune to water (IP44), extreme temperatures and oils
- Power extension cable reel with thermal fuse
- stable stand, reel and rubber-coated grip

length: 25 m ▪ conductor cross section: 1.5 mm² ▪ voltage: 230 V~/400 V~ ▪ current: 13 A ▪ IP rating: IP44 ▪ number of sockets: 1 ▪ thermal fuse ▪ conductor: H07RN-F ▪ max. reeled load: 230 V~: 4.35 A max./1 000 W; 400 V~: 6.25 A max./2 500 W ▪ max. unreeled load: 230 V~: 13 A max./3 000 W; 400 V~: 12.5 A max./5 000 W ▪ children protection: no ▪ packaging: 1 pc, box





25 m

H07RN-F 1,5 mm²

IP44

8 592920 025062

P192250 1/-/-/1

19 28 432 500 E-102A

length: 33 m ▪ conductor cross section: 2.5 mm² ▪ voltage: 230 V~/400 V~ ▪ current: 15 A ▪ IP rating: IP44 ▪ number of sockets: 1 ▪ thermal fuse ▪ conductor: H07RN-F ▪ max. reeled load: 230 V~: 6.52 A max./1 500 W; 400 V~: 6.25 A max./2 500 W ▪ max. unreeled load: 230 V~: 15.22 A max./3 500 W; 400 V~: 16 A max./6 400 W ▪ children protection: no ▪ packaging: 1 pc, box





33 m

H07RN-F 2,5 mm²

IP44

8 592920 028896

P19733 1/-/-/1

19 28 733 300 EM7-533 IP44 440V (E-017)