


TM.PRIMO G

LEAVES NO DOUBT

- » high luminance – up to 500 cd/m²
- » up to 2 sizes
- » visibility up to 40 meters



- » extended lifetime thanks to LiFePO₄ packages
- » one-sided or double-sided view fitting



100

Dimensions [± 2 mm]



30



	a	b
» TM.PRIMO G 30	301	219
» TM.PRIMO G 40	401	269

Application	evacuation road direction (evacuation sign)
Light source	LED
Battery	LiFePO4
Testing for self-contained	non-addressable: ST – for button test non-addressable: AT – auto-test / self-test addressable: DATA – with addressable module for DATA system addressable: DATA 2 – with addressable module for DATA 2 system addressable: DALI – with addressable module for DALI systems
Testing for central battery	non-addressable: CB – without addressable module addressable : CBA – with addressable module
Power supply	210÷250 V AC 50÷60 Hz 186÷254 V DC
Protection degree	IP20
Insulation class	I
Temperature range	ST, AT, DATA, DATA 2, DALI: $t_a +10^{\circ}\text{C} \div +35^{\circ}\text{C}$ CB: $t_a -15^{\circ}\text{C} \div +55^{\circ}\text{C}$ CBA: $t_a -10^{\circ}\text{C} \div +40^{\circ}\text{C}$
Glow wire test	850°C
Colour	<input checked="" type="checkbox"/> - stainless steel <input type="checkbox"/> RAL 9003 <input checked="" type="checkbox"/> RAL 9005 - black steel
Material	housing: stainless steel (polished/brushed) or RAL 9003 / RAL 9005 powder coated black steel

Pictograms in the set:



Model	Type	Visibility	Luminance	Mode	Time	Testing
TM.PRIMO G 30E	one-sided	30 m	$\geq 150 \text{ cd/m}^2$	M / NM	3 h	ST / AT / DATA / DALI
TM.PRIMO G 40E	one-sided	40 m	$\geq 150 \text{ cd/m}^2$	M / NM	3 h	ST / AT / DATA / DALI
TM.PRIMO G 30E	one-sided	30 m	$\geq 150 \text{ cd/m}^2$	-	-	CB, CBA
TM.PRIMO G 40E	one-sided	40 m	$\geq 150 \text{ cd/m}^2$	-	-	CB, CBA