

Reference table	
Present types	New types
RD 9123	RK 0203 T
RD 9125	RK 0205 T
RD 9127	RK 0207 T
RD 9045	RK 0405 T
RD 9041	RK 0610 T
RK 9062	RK 0612 T
RK 9064	RK 0614 T
RK 9109	RK 1019 T
RK 9104	RK 1024 T

DK Cable junction boxes

With terminal blocks for aluminum and copper conductors

Cable entry via integrated elastic membranes or metric knockouts

- Terminal marking, neutral
- With elastic membrane, which can be removed for cable entry via cable glands
- Multi-level knockouts for cable glands in different sizes
- Cable entry through the bottom of the box via integrated elastic membrane
- Closes quickly by a quarter turn - locked position well visible (open - locked)
- Lid fasteners sealable without accessories
- External brackets for wall fixing included
- Retaining strap, details see product description
- Labelling system for circuit description
- All terminals with two clamping units per pole
- Terminals prevent damage of conductors, also with flexible conductors without ferrule
- Material: polypropylene
- Burning behaviour:
glow wire test in accordance with IEC 60695-2-11: 750 °C,
flame-retardant, self-extinguishing
- Colour: grey, RAL 7035

DK Cable junction boxes

with terminal blocks for aluminum and copper conductors, cable entry via integrated elastic membranes or metric knockouts





RK 1019 T NEW

1.5-4 mm²

- 19 terminal blocks WK 4/U
- per terminal 2 x 0,5-4 mm² f, 2 x 0,5-6 mm² sol or 2 x 1,5-4 mm² s, see Technical details DK cable junction boxes for more information about terminal assignment
- terminal blocks, by Wieland
- for aluminium and copper conductors
- terminal marking, neutral
- with elastic membranes, which can be removed for cable entry via cable glands, sealing range 9.0-21.0 mm
- with two cable entries in the bottom, sealing range Ø 9.0-20.0 mm
- lid fasteners sealable without accessories
- retaining strap and external brackets for wall fixing included

IP
66



rated insulation voltage	$U_i = 690 \text{ V a.c./d.c.}$
current carrying capacity	41 A
tightening torque for terminal material	0.5 Nm
	PP (polypropylene)





RK 1024 T NEW

1.5-4 mm²

- 24 terminal blocks WK 4/U
- per terminal 2 x 0,5-4 mm² f, 2 x 0,5-6 mm² sol or 2 x 1,5-4 mm² s, see Technical details DK cable junction boxes for more information about terminal assignment
- terminal blocks, by Wieland
- for aluminium and copper conductors
- terminal marking, neutral
- with elastic membranes, which can be removed for cable entry via cable glands, sealing range 9.0-21.0 mm
- with two cable entries in the bottom, sealing range Ø 9.0-20.0 mm
- lid fasteners sealable without accessories
- retaining strap and external brackets for wall fixing included

IP
66



rated insulation voltage	$U_i = 690 \text{ V a.c./d.c.}$
current carrying capacity	41 A
tightening torque for terminal material	0.5 Nm
	PP (polypropylene)