

monitoring relays – multifunctions

# RPN-1A..-A230

CE EAC



RPN-1A16-A230

AC current monitoring in 1-phase network, with adjustable thresholds



## RPN-1A..-A230 ④

Number & type of contacts	1 CO	
Rated load	AC1	12 A / 250 V AC
	DC1	12 A / 24 V DC ①
Rated input voltage	AC	50/60 Hz: 230 V
Dimensions	mm	90(98,8) x 17,5 x 64,6 ②
Terminals	universal screw terminals ③	

monitoring relays – single-functions

# RPN-1TMP-A230

CE EAC



RPN-1TMP-A230

motor temperature monitoring



## RPN-1TMP-A230

Number & type of contacts	1 CO	
Rated load	AC1	12 A / 250 V AC
	DC1	12 A / 24 V DC ①
Rated input voltage	AC	50/60 Hz: 230 V
Dimensions	mm	90(98,8) x 17,5 x 64,6 ②
Terminals	universal screw terminals ③	

① DC1: 0,3 A / 250 V DC    ② In the bracket the length with 35 mm rail catches is shown  
 ③ Cross-recessed or slotted head screw    ④ 6 versions of relays - measuring inputs: 0,5 A, 1 A, 2 A, 5 A, 8 A, 16 A