

# VOLTAGE STABILIZER

## Technical Characteristic

- Input Voltage : 175/265V
  - Output Voltage : 220V
- Çift 00 olan eklencek mi??

## Technical Characteristic

- Input Voltage : 150/250V
- Output Voltage : 220V

### Single-Phase Micro Processor Electronic

| Code       | Protected   | Power (K.VA.) | Characteristic of Product |
|------------|-------------|---------------|---------------------------|
| S11 C1Y 00 | S11 C1KY 00 | 1             | Copper Wired              |
| S11 C1Y 01 | S11 C1KY 01 | 2             | Copper Wired              |
| S11 C1Y 02 | S11 C1KY 02 | 3.5           | Copper Wired              |
| S11 C1Y 03 | S11 C1KY 03 | 5             | Copper Wired              |
| S11 C1Y 04 | S11 C1KY 04 | 7.5           | Copper Wired              |
| S11 C1Y 05 | S11 C1KY 05 | 10            | Copper Wired              |
| S11 C1Y 06 | S11 C1KY 06 | 15            | Copper Wired              |
| S11 C1Y 07 | S11 C1KY 07 | 20            | Copper Wired              |
| S11 C1Y 08 | S11 C1KY 08 | 25            | Copper Wired              |
| S11 C1Y 09 | S11 C1KY 09 | 30            | Copper Wired              |
| S11 C1Y 10 | S11 C1KY 10 | 40            | Copper Wired              |
| S11 C1Y 11 | S11 C1KY 11 | 50            | Copper Wired              |



### Single-Phase Micro Processor Electronic

| Code       | Protected   | Power (K.VA.) | Characteristic of Product |
|------------|-------------|---------------|---------------------------|
| S11 C1N 00 | S11 C1KN 00 | 1             | Copper Wired              |
| S11 C1N 01 | S11 C1KN 01 | 2             | Copper Wired              |
| S11 C1N 02 | S11 C1KN 02 | 3.5           | Copper Wired              |
| S11 C1N 03 | S11 C1KN 03 | 5             | Copper Wired              |
| S11 C1N 04 | S11 C1KN 04 | 7.5           | Copper Wired              |
| S11 C1N 05 | S11 C1KN 05 | 10            | Copper Wired              |
| S11 C1N 06 | S11 C1KN 06 | 15            | Copper Wired              |
| S11 C1N 07 | S11 C1KN 07 | 20            | Copper Wired              |
| S11 C1N 08 | S11 C1KN 08 | 25            | Copper Wired              |
| S11 C1N 09 | S11 C1KN 09 | 30            | Copper Wired              |
| S11 C1N 10 | S11 C1KN 10 | 40            | Copper Wired              |
| S11 C1N 11 | S11 C1KN 11 | 50            | Copper Wired              |

## KORUMALI KODLAR EKLENDİ

## Technical Characteristic

- Input Voltage : 300/460V
- Output Voltage : 380V

## Technical Characteristic

- Input Voltage : 260/450V
- Output Voltage : 380V

### Three-Phase Micro Processor Electronic

| Code       | Protected   | Power (K.VA.) | Characteristic of Product |
|------------|-------------|---------------|---------------------------|
| S11 C3Y 01 | S11 C3KY 01 | 6             | Copper Wired              |
| S11 C3Y 02 | S11 C3KY 02 | 10.5          | Copper Wired              |
| S11 C3Y 03 | S11 C3KY 03 | 15            | Copper Wired              |
| S11 C3Y 04 | S11 C3KY 04 | 22.5          | Copper Wired              |
| S11 C3Y 05 | S11 C3KY 05 | 30            | Copper Wired              |
| S11 C3Y 06 | S11 C3KY 06 | 45            | Copper Wired              |
| S11 C3Y 07 | S11 C3KY 07 | 60            | Copper Wired              |
| S11 C3Y 08 | S11 C3KY 08 | 75            | Copper Wired              |
| S11 C3Y 09 | S11 C3KY 09 | 100           | Copper Wired              |
| S11 C3Y 10 | S11 C3KY 10 | 120           | Copper Wired              |
| S11 C3Y 11 | S11 C3KY 11 | 150           | Copper Wired              |
| S11 C3Y 12 | S11 C3KY 12 | 200           | Copper Wired              |
| S11 C3Y 13 | S11 C3KY 13 | 250           | Copper Wired              |
| S11 C3Y 14 | S11 C3KY 14 | 300           | Copper Wired              |
| S11 C3Y 15 | S11 C3KY 15 | 400           | Copper Wired              |
| S11 C3Y 16 | S11 C3KY 16 | 500           | Copper Wired              |
| S11 C3Y 17 | S11 C3KY 17 | 600           | Copper Wired              |
| S11 C3Y 18 | S11 C3KY 18 | 800           | Copper Wired              |
| S11 C3Y 19 | S11 C3KY 19 | 1000          | Copper Wired              |
| S11 C3Y 20 | S11 C3KY 20 | 1200          | Copper Wired              |
| S11 C3Y 21 | S11 C3KY 21 | 1600          | Copper Wired              |
| S11 C3Y 22 | S11 C3KY 22 | 2000          | Copper Wired              |
| S11 C3Y 23 | S11 C3KY 23 | 2500          | Copper Wired              |
| S11 C3Y 24 | S11 C3KY 24 | 3250          | Copper Wired              |



### Three-Phase Micro Processor Electronic

| Code       | Protected   | Power (K.VA.) | Characteristic of Product |
|------------|-------------|---------------|---------------------------|
| S11 C3N 26 | S11 C3KN 26 | 6             | Copper Wired              |
| S11 C3N 27 | S11 C3KN 27 | 10.5          | Copper Wired              |
| S11 C3N 28 | S11 C3KN 28 | 15            | Copper Wired              |
| S11 C3N 29 | S11 C3KN 29 | 22.5          | Copper Wired              |
| S11 C3N 30 | S11 C3KN 30 | 30            | Copper Wired              |
| S11 C3N 31 | S11 C3KN 31 | 45            | Copper Wired              |
| S11 C3N 32 | S11 C3KN 32 | 60            | Copper Wired              |
| S11 C3N 33 | S11 C3KN 33 | 75            | Copper Wired              |
| S11 C3N 34 | S11 C3KN 34 | 100           | Copper Wired              |
| S11 C3N 35 | S11 C3KN 35 | 120           | Copper Wired              |
| S11 C3N 36 | S11 C3KN 36 | 150           | Copper Wired              |
| S11 C3N 37 | S11 C3KN 37 | 200           | Copper Wired              |
| S11 C3N 38 | S11 C3KN 38 | 250           | Copper Wired              |
| S11 C3N 39 | S11 C3KN 39 | 300           | Copper Wired              |
| S11 C3N 40 | S11 C3KN 40 | 400           | Copper Wired              |
| S11 C3N 41 | S11 C3KN 41 | 500           | Copper Wired              |
| S11 C3N 42 | S11 C3KN 42 | 600           | Copper Wired              |
| S11 C3N 43 | S11 C3KN 43 | 800           | Copper Wired              |
| S11 C3N 44 | S11 C3KN 44 | 1000          | Copper Wired              |
| S11 C3N 45 | S11 C3KN 45 | 1200          | Copper Wired              |
| S11 C3N 46 | S11 C3KN 46 | 1600          | Copper Wired              |
| S11 C3N 47 | S11 C3KN 47 | 2000          | Copper Wired              |
| S11 C3N 48 | S11 C3KN 48 | 2500          | Copper Wired              |
| S11 C3N 49 | S11 C3KN 49 | 3250          | Copper Wired              |