










Fișe cilindrice izolate



TRACON	d ₁ (mm)	d ₂ (mm)	D (mm)	L (mm)	I (mm)	mm ²			
■ PH4	1.7	4	4.7	22.6	9	1-2.5	1-1.5	0.75-1	 RELEVANT STANDARD EN 61238-1
■ KH4	2.2	5	5.5	22	9	2.5	1.5-2.5	1.5	
■ SH4	3.6	5	7.5	24.3	9	6	4-6	4	











 E-Cu-sn
 PVC
 Ta
 -20...+75 °C




Mufe cilindrice izolate



TRACON	d ₁ (mm)	d ₂ (mm)	D (mm)	L (mm)	mm ²			
■ PHA4	1.8	4	5.5	23.8	1-2.5	1-1.5	0.5-1.5	 RELEVANT STANDARD EN 61238-1
■ KHA4	2.1	5	6	23	2.5	1.5-2.5	1.5	
■ SHA4	3.5	5	7.4	25	6	4-6	4	











 E-Cu-sn
 PVC
 Ta
 -20...+75 °C



Papuci tip pin izolați

TRACON	d ₁ (mm)	D (mm)	L (mm)	I ₁ (mm)	B (mm)	mm ²			
■ PCS	1.8	5.4	23.3	12	1.9	1-2.5	1-1.5	0.5-1.5	 RELEVANT STANDARD MSZ-05-45.1601-1 MSZ-05-45.1601-21
■ KCS	2.3	6	23.3	12	1.9	2.5-4	1.5-2.5	1.5-2.5	
■ SCS	3.5	7.8	28.5	13	2.7	6	4-6	4	

 E-Cu-sn
 PVC
 Ta
 -20...+75 °C

