





## **Infrared Sensor**

Sensor Type: Colour: **Detection Range:** Voltage: **Detection Distance:** Rated Load: Ambient Light: Body Type: IP Rating: Dimension: Time Delay: Box Qty:

VT-8051

SKU: 1356 Infrared White 360° AC:220-240V.50/60Hz Max. 6m(<24°C) Max 300W(LED) <3-2000LUX(adjustable) PC IP20 76×75.6mm Min. 10sec±3sec, Max. 15min±2min 50 Pcs

#### 1. Automatic Sensor Override Mode - Turn the switch OFF and ON within 3 Seconds, the sensor will be overridden and switched off. The light will work continuously and normally. (Make sure the automatic mode is switched ON before using this functionality).

2. Sensor Switch On - Turn the switch OFF for 20 seconds and switch it back ON. The sensor will restart and work as per the settings adjusted. 3. If the light is left idle for a longer period, the sensor will automatically switch back to automatic mode (Possible when the outside light reaches 100Lux).



# Day Light Sensor – 1–10V

### SKU: 1369

Sensor Type: Colour: Detection Range: Voltage: Body Type: IP Rating: Box Qty:

VT-8059

Day Light White 360° DC:1-10V PC IP20 100 Pcs

Daylight Sensor supplies a simple and effective solution for daylight harvesting. Connecting to 1–10V Power source and using with LED dimmable driver. The illumination level of lamps will

get darker when ambient light gets brighter.

When daylight is insufficient, the lamp will be in 100% Illumination level, and turns to 1% Level when daylight is sufficient, then gradually bac




## **Infrared Sensor** SKU: 15011

VT-8083-B



Sensor Type: Infrared Colour: Black Body Type: PC IP Rating: IP65 **Detection Range:** 360° Detection Distance: Max.20m(<24°C)

Voltage: Dimension: Time Delay: Box Qty:



Ambient Light: <3-2000LUX (adjustable) AC:220-240V,50/60Hz 86.5×172.5×56mm Min.10sec±3sec, Max. 30min±2min 50 Pcs 1000w(LED) Rated Load:




#### **Infrared Sensor** SKU: 15001 VT-8083-W



Infrared Sensor Type: White Colour: PC Body Type: IP Rating: IP65 **Detection Range:** 360° Detection Distance: Max.20m(<24°C)

Voltage: Dimension: Time Delay: Box Qty: Rated Load:



Ambient Light: <3-2000LUX (adjustable) AC:220-240V,50/60Hz 86.5×172.5×56mm Min.10sec±3sec, Max. 30min±2min 50 Pcs 1000w(LED)





