



## LED BATTEN FITTING | Opaque Cover - M Series SS Clips

Promoting efficiency with its high-lumen (120 lm/W) rating, this new addition to V-TAC's fixtures range is reinforced with secure, stainless steel clips for easier maintenance. The opaque cover allows a brighter, well-distributed light that is perfect for task lighting.



- SMD LED Chip
- 20,000 hrs Lifespan
- 120° Beam Angle
- AC:200-240V,50/60Hz
- On/Off Cycles >15000
- Body Type: PC
- CRI >80
- PF >0.9
- IP65
- SS Clips










Model	sкu	Watts	Lumen	Dimension	Box Qty
<u>VT-120136-T</u>	20219   4000K DAY WHITE 20218   6400K WHITE	36W	4320	1200mm N 78	12 pcs

VT-150148-T

20213 | 4000K DAY WHITE 20212 | 6400K WHITE

48w 5760



12 pcs

## **Microwave Sensor**



6622

- Rod antenna DIP Switch
- Max Watts: 100W
- Hold Time: 5s/1min/3min/10min
- Daylight threshold: 30Lux/Disable
- Detection Area: 50%/100%
- Automatic On/Off control with daylight sensor.
- Optional detection range, hold time and daylight threshold.
- Loop in and loop out for easy installation.
- Operating Voltage: AC:220-240V, 50/60Hz
- Detection Range: ø4-10m/13.12-32.8ft (ceiling mounted)
- Compatible with V-TAC's LED Waterproof Fitting M Series SS Clips