



LED DOME LIGHTS | Slim Domelight with Emergency Backup

- AC:220-240V,50/60Hz
- 110° Beam Angle
- SMD LED chip type
- PC Body
- 30,000 Life Hours
- CRI >80
- Battery type -Ni-Cd 9.6V,1.0Ah
- Battery Charging Current – 60mA
- Battery Discharge Current – 200mA
- > 3 Hours emergency operation time
- IP65 Rating



3 YEAR
WARRANTY




IP65
RATING



Emergency
Battery Backup



Model	SKU	Watts	Lumen	Dimension	Box Qty
<u>VT-12SE</u>	822 4000K DAY WHITE	14w	1440		10 pcs

LED DOME LIGHTS | Slim Domelight with Sensor

- 360°Ceiling/120°Wall Mounted
- Detection Motion Speed – 0.5-3m/s
- Hold Time – 30s, 40s, 50s customized
- Daylight sensor -Day, 2lux, 10lux, 50lux optional
- Dimmable – Yes, 0, 10%,20% optional
- Manual Override by dial switch
- Stand by period – 0s, 10s, 10m optional
- AC:220-240V,50/60Hz
- 110° Beam Angle
- 30,000 Life Hours
- CRI >80
- Microwave Sensor
- 3-6m detection distance
- 10mx6m detection range



5 YEAR
WARRANTY




IP54
RATING



Microwave
Sensor



Model	SKU	Watts	Lumen	Dimension	Box Qty
<u>VT-12SS</u>	937 3000K WARM WHITE 821 4000K DAY WHITE 938 6400K DAY WHITE	12w	1440		10 pcs

LED DOME LIGHTS | Slim Domelight with Emergency+Sensor

- 3-6m detection distance
- 10mx6m detection range
- 360°Ceiling/120°Wall Mounted
- 0.5-3m/s detection motion speed
- 30s, 40s, 50s customized (time delay)
- Daylight sensor -Day: 7-20LUX
- Dimmable – Yes, 0, 10%,20% optional
- Manual Override
- Standby – 0s, 10s, 10m optional
- > 3 Hours emergency operation time
- Battery type -Ni-Cd 9.6V,1.0Ah
- Battery Charging Current – 60mA
- Battery Discharge Current – 200mA
- AC:220-240V,50/60Hz
- 110° Beam Angle
- 30,000 Life Hours



3 YEAR
WARRANTY



IP54
RATING



Bulkhead
Emergency
Battery Backup
Microwave Sensor



Model	SKU	Watts	Lumen	Dimension	Box Qty
<u>VT-12SES</u>	823 4000K DAY WHITE	14w	1440		10 pcs