










Mufe izolate


TRACON	d ₁ (mm)	D (mm)	L (mm)				mm ²	
PTH	2	6	25	1-2.5	0.5-1.5	0.5-1.5		9006; 9006R; 9006RS
KTH	2.7	6.5	25	2.5-4	1.5-2.5	1.5-2.5		
STH	3.9	8	27	4-6	4-6	4		










RELEVANT STANDARD
MSZ-05-45.1601-1
MSZ-05-45.1601-21











Mufe cu izolație termocontractabilă


TRACON	d ₁ (mm)	D (mm)	L (mm)				mm ²	
ZSTHP	1.8	4.6	37	1-1.5	0.5-1.5	0.75-1		9006; 9006R; 9006RS
ZSTHK	2.6	5.4	36.6	2.5-4	1.5-2.5	1.5-2.5		
ZSTHS	3.6	6.6	42	4-6	4-6	2.5-4		







RELEVANT STANDARD
MSZ-05-45.1601-1
MSZ-05-45.1601-21



Manșon termocontractabil cu staniu

TRACON	d ₁ (mm)	D (mm)	L (mm)		mm ²
THSN0,5	2	2.5	24		0.5-1
THSN1	2.6	4.4	40		1-1.5
THSN2,5	4.2	6.2	42		2.5-4
THSN6	6	7	40		4-6

