



VE118PN

Enclosure,vector,surface mounted,IP65,18M,UV stable,with metric cable entry

Technical properties

Architecture

Fixing mode	surface-mounting
-------------	------------------

Functions

With a pipe-in lead	Yes
---------------------	-----

Configuration

Number of modules	18
-------------------	----

Compatibility

Suitable for Multimedia	No
-------------------------	----

Voltage

Rated operational voltage in DC	1000 V DC
---------------------------------	-----------

Electric current

Rated current	63 A
---------------	------

Dimensions

Depth of installed product	151 mm
----------------------------	--------

Internal depth	151 mm
----------------	--------

Height of installed product	302 mm
-----------------------------	--------

Width of installed product	418 mm
----------------------------	--------

Width in division units	18
-------------------------	----

Thickness of sidewall material	2.5 mm
--------------------------------	--------

Cover, door

Type of door closing	Latch
----------------------	-------

Identification od protection index	65
------------------------------------	----

Interlockable	No
---------------	----

Number of keylock of the door	0
-------------------------------	---

Cover type	Closed (plain)
------------	----------------

Door locking	without
--------------	---------

Door leave	single
------------	--------

Cover type	Door
------------	------

Transparent cover or door	Yes
---------------------------	-----

Materials

Colour	light grey
--------	------------

Colour	light grey
--------	------------

RAL colour	RAL 7035 - Light grey
------------	-----------------------

Subject to technical modifications

Type of surface treatment	untreated
Installation, mounting	
Suitable for outdoor use	Yes
Connection	
Number of conduit inlets	15
Settings	
Enclosure type	Distributor empty cabinet
Equipment	
Number of rows	1
Quantity of section in width	1
Quantity of rails	1
Can be accessorized	Yes
Extension possible	No
Earthing terminal block	No
Neutral terminal block	No
Signal passing door	Yes
Standards	
GWT Glow wire test	850 °C
Safety	
Protection class	isol.class II
Glow wire test	according EN 60695-2-11: 850°C
REACH conform	No
RoHS conform	Yes
Use conditions	
Operating temperature	-25...40 °C