



www.emos.eu

Order Code
Item Number

Packaging
Type

- power: 24 W
- replacement of incandescent bulb: 125 W
- luminous flux: 2 000 lm
- color temperature: 3 000 K
- body material: aluminum
- color rendering index (CRI): Ra > 80
- beam angle: 120°
- sensor detection range: no sensor
- luminaire type: built-in

- dimensions: 297 × 21 mm in diameter
- mounting hole: 285 mm
- body colour: white
- warranty period: 3 years



ZD1151 1/-/-/4
15 40 112 410 ZD1151

- power: 24 W
- replacement of incandescent bulb: 125 W
- luminous flux: 2 000 lm
- color temperature: 4 000 K
- body material: aluminum
- color rendering index (CRI): Ra > 80
- beam angle: 120°
- sensor detection range: no sensor
- luminaire type: built-in

- dimensions: 297 × 21 mm in diameter
- mounting hole: 280 mm
- body colour: white
- warranty period: 3 years



ZD1152 1/-/-/4
15 40 112 420 ZD1152

- power: 6 W
- replacement of incandescent bulb: 40 W
- luminous flux: 450 lm
- color temperature: 4 000 K
- body material: aluminum
- color rendering index (CRI): Ra > 80
- beam angle: 120°
- sensor detection range: no sensor
- luminaire type: built-in

- dimensions: 120 × 21 mm in diameter
- mounting hole: 105 mm
- body colour: silver
- warranty period: 3 years



ZD1222 1/-/4/16
15 40 120 670 ZD1222

- power: 12 W
- replacement of incandescent bulb: 70 W
- luminous flux: 1 000 lm
- color temperature: 4 000 K
- body material: aluminum
- color rendering index (CRI): Ra > 80
- beam angle: 120°
- sensor detection range: no sensor
- luminaire type: built-in

- dimensions: 175 × 21 mm in diameter
- mounting hole: 155 mm
- body colour: silver
- warranty period: 3 years



ZD1232 1/-/4/8
15 40 121 270 ZD1232

- power: 18 W
- replacement of incandescent bulb: 100 W
- luminous flux: 1 500 lm
- color temperature: 4 000 K
- body material: aluminum
- color rendering index (CRI): Ra > 80
- beam angle: 120°
- sensor detection range: no sensor
- luminaire type: built-in

- dimensions: 225 × 21 mm in diameter
- mounting hole: 205 mm
- body colour: silver
- warranty period: 3 years



ZD1242 1/-/4/16
15 40 121 870 ZD1242