

## Suspended square white, silver

- 4 input power options – 6 W, 12 W, 18 W or 24 W
- aluminium body and plastic diffuser, white or silver frame
- light: warm or neutral white
- high quality LIFUD drivers
- simple installation
- 3 year warranty

- power: 6 W
- replacement of incandescent bulb: 40 W
- luminous flux: 450 lm
- color temperature: 3 000 K
- body material: aluminum
- color rendering index (CRI): Ra > 80
- beam angle: 120°
- sensor detection range: no sensor
- luminaire type: attached

**ZM6121**

1/-/-16

15 39 061 050

ZM6121

- power: 12 W
- replacement of incandescent bulb: 70 W
- luminous flux: 1 000 lm
- color temperature: 3 000 K
- body material: aluminum
- color rendering index (CRI): Ra > 80
- beam angle: 120°
- sensor detection range: no sensor
- luminaire type: attached

**ZM6131**

1/-/4/16

15 39 061 060

ZM6131

- power: 18 W
- replacement of incandescent bulb: 100 W
- luminous flux: 1 500 lm
- color temperature: 3 000 K
- body material: aluminum
- color rendering index (CRI): Ra > 80
- beam angle: 120°
- sensor detection range: no sensor
- luminaire type: attached

**ZM6141**

1/-/4/8

15 39 061 070

ZM6141

- power: 24 W
- replacement of incandescent bulb: 125 W
- luminous flux: 2 000 lm
- color temperature: 3 000 K
- body material: aluminum
- color rendering index (CRI): Ra > 80
- beam angle: 120°
- sensor detection range: no sensor
- luminaire type: attached

**ZM6151**

1/-/-/4

15 39 061 080

ZM6151