

- power: 36 W
- replacement of incandescent bulb: 4× 18 W CFL
- luminous flux: 3 600 lm
- color temperature: 2 700–6 000 K
- body material: aluminum
- color rendering index (CRI): Ra > 80
- beam angle: 90°
- sensor detection range: no sensor
- luminaire type: recessed
- dimensions: 595 × 595 × 10 mm
- dimming function
- body colour: white
- line: PROFI
- warranty period: 3 years
- UGR<: 19

**ZR5410**

1/-/-/4

15 44 213 670

ZR5410

- power: 18 W
- replacement of incandescent bulb: 2× 18 W CFL
- luminous flux: 1 900 lm
- color temperature: 4 000 K
- body material: aluminum
- color rendering index (CRI): Ra > 80
- beam angle: 120°
- sensor detection range: no sensor
- luminaire type: recessed
- dimensions: 595 × 295 × 10,4 mm
- body colour: white
- line: PROFI PLUS
- warranty period: 5 years
- UGR<: 22

**ZR2212**

1/-/-/8

15 41 181 200

ZR2212

- product: frame for surface installation
- dimensions: 600 × 600 × 45 mm
- material: aluminum
- designed for: LED panel 60 × 60
- packaging: 1 ks, box

**ZR9034**

1/-/-/20

15 42 009 034

ZR9034

- product: frame for surface installation
- dimensions: 1 200 × 300 × 45 mm
- material: aluminum
- designed for: LED panel 30 × 120
- packaging: 1 ks, box

**ZR9035**

1/-/-/15

15 42 009 035

ZR9035