

**ZR9010** 1/-/-/100  
15 42 009 010 ZR9010



- product: set of hooks
- designed for: LED panel 60×60 (30)



**ZR9011** 1/-/-/100  
15 42 009 011 ZR9011



- product: set of hooks
- designed for: LED panel 30 ×120



**ZR9020** 1/-/-/100  
15 42 009 020 ZR9020



- product: set of ropes
- designed for: LED panel 60×60 (30)



**ZR9021** 1/-/-/100  
15 42 009 021 ZR9021



- product: set of ropes
- designed for: LED panel 30 ×120



**ZR9034** 1/-/-/20  
15 42 009 034 ZR9034




- dimensions: 620 × 620 × 50 mm
- material: aluminum
- packaging: 1 ks, box



**ZR9035** 1/-/-/15  
15 42 009 035 ZR9035



- dimensions: 1 213 × 313 × 47 mm
- material: aluminum
- packaging: 1 ks, box



## LED drivers

- universal supply for dimming LED lights
- source of constant current, supports log. & linear waveforms
- synchronised dimming – 1 supply controls up to 7 others
- adjustable current output via DIP switches (350–1 050 mA)
- 5 year warranty

- voltage input: 180–264 V AC
- frequency: 50/60 Hz
- output voltage: 30–57 V DC
- output current: 350–1 050 mA
- power: 16–40 W
- dimensions: 124.5 × 82.5 × 25.4 mm
- type: MULTI
- warranty period: 5 years



**ZR9080** 1/-/-/36  
15 60 019 900 ZR9080