



www.emos.eu

Order Code
Item Number

Packaging
Type

- power: 100 W
- luminous flux: 13 000 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 100–240 V
- IP rating: IP65
- beam angle: 120 × 90°
- dimensions: 321 × 280 × 85 mm

- supply cable length: 1 m
- lead-in cable material: rubber
- lead-in cable type: H05RN-F
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box



ZS2452 1/-/-/1
15 31 245 200 ZS2452

- power: 150 W
- luminous flux: 20 000 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 100–240 V
- IP rating: IP65
- beam angle: 120 × 90°
- dimensions: 321 × 280 × 85 mm

- supply cable length: 1 m
- lead-in cable material: rubber
- lead-in cable type: H05RN-F
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box



ZS2462 1/-/-/1
15 31 246 200 ZS2462

- power: 300 W
- luminous flux: 40 000 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 100–240 V
- IP rating: IP65
- beam angle: 120 × 90°
- dimensions: 321 × 465 × 95 mm

- supply cable length: 1 m
- lead-in cable material: rubber
- lead-in cable type: H05RN-F
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box



ZS2472 1/-/-/1
15 31 247 200 ZS2472

ASIMO

- SMD technology
- luminous efficacy of up to 110 lm/W
- Al body, rubber lead-in cable
- IP66 – suitable for outdoors
- shape and width of light cone optimized for specific applications
- unique design, easy installation via mount
- diffuser material: glass
- 5 year warranty

- power: 50 W
- luminous flux: 5 500 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220–240 V~
- IP rating: IP66
- beam angle: 55 × 125°
- dimensions: 190 × 200 × 55 mm

- supply cable length: 1 m
- lead-in cable material: rubber
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box



ZS1050A 1/-/-/1
15 31 105 000 ZS1050A