



www.emos.eu

Order Code  
Item Number

Packaging  
Type

- power: 50 W
- luminous flux: 5 500 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220-240 V~
- IP rating: IP66
- beam angle: 26 × 60°
- dimensions: 190 × 200 × 55 mm

- supply cable length: 1 m
- lead-in cable material: rubber
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box



**ZS1050B**

1/-/-1

15 31 105 001

ZS1050B

- power: 50 W
- luminous flux: 5 500 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220-240 V~
- IP rating: IP66
- beam angle: 60°
- dimensions: 190 × 200 × 55 mm

- supply cable length: 1 m
- lead-in cable material: rubber
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box



**ZS1050N**

1/-/-1

15 31 105 002

ZS1050N

- power: 100 W
- luminous flux: 11 000 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220-240 V~
- IP rating: IP66
- beam angle: 55 × 125°
- dimensions: 230 × 240 × 61 mm

- supply cable length: 1 m
- lead-in cable material: rubber
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box



**ZS1100A**

1/-/-1

15 31 110 000

ZS1100A

- power: 100 W
- luminous flux: 11 000 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220-240 V~
- IP rating: IP66
- beam angle: 26 × 60°
- dimensions: 230 × 240 × 61 mm

- supply cable length: 1 m
- lead-in cable material: rubber
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box



**ZS1100B**

1/-/-1

15 31 110 001

ZS1100B

- power: 100 W
- luminous flux: 11 000 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220-240 V~
- IP rating: IP66
- beam angle: 60°
- dimensions: 230 × 240 × 61 mm

- supply cable length: 1 m
- lead-in cable material: rubber
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box



**ZS1100N**

1/-/-1

15 31 110 002

ZS1100N