



www.emos.eu

Order Code
Item Number

Packaging
Type

- power: 200 W
- luminous flux: 22 000 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220-240 V~
- IP rating: IP66
- beam angle: 55 × 125°
- dimensions: 300 × 305 × 70 mm

- supply cable length: 1 m
- lead-in cable material: rubber
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box



ZS1200A 1/-/-/1
15 31 120 000 ZS1200A

- power: 200 W
- luminous flux: 22 000 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220-240 V~
- IP rating: IP66
- beam angle: 26 × 60°
- dimensions: 300 × 305 × 70 mm

- supply cable length: 1 m
- lead-in cable material: rubber
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box



ZS1200B 1/-/-/1
15 31 120 001 ZS1200B

- power: 200 W
- luminous flux: 22 000 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220-240 V~
- IP rating: IP66
- beam angle: 60°
- dimensions: 300 × 305 × 70 mm

- supply cable length: 1 m
- lead-in cable material: rubber
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box



ZS1200N 1/-/-/1
15 31 120 002 ZS1200N

- power: 300 W
- luminous flux: 33 000 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220-240 V~
- IP rating: IP66
- beam angle: 55 × 125°
- dimensions: 363 × 370 × 80 mm

- supply cable length: 1 m
- lead-in cable material: rubber
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box



ZS1300A 1/-/-/1
15 31 130 000 ZS1300A

- power: 300 W
- luminous flux: 33 000 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220-240 V~
- IP rating: IP66
- beam angle: 26 × 60°
- dimensions: 363 × 370 × 80 mm

- supply cable length: 1 m
- lead-in cable material: rubber
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box



ZS1300B 1/-/-/1
15 31 130 001 ZS1300B