



www.emos.eu

Order Code
Item Number

Packaging
Type

- power: 300 W
- luminous flux: 33 000 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220–240 V~
- IP rating: IP66
- beam angle: 60°
- dimensions: 363 × 370 × 80 mm
- supply cable length: 1 m
- lead-in cable material: rubber
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box



ZS130N 1/-/-/1
15 31 130 002 ZS130N

Luminaires

Floodlights

PROFI

INOVO

- SMD technology
- luminous efficacy of up to 110 lm/W
- aluminium body, rubber lead-in cable
- IP65 – suitable for outdoors
- PIR sensor detection angle: 180°
- neutral white light, glass diffuser
- lead-in cable with plastic connector
- 5 year warranty

- power: 10 W
- luminous flux: 1 100 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220–240 V~
- IP rating: IP65
- beam angle: 120°
- dimensions: 95 × 70 × 27 mm
- supply cable length: 30 cm
- lead-in cable material: rubber
- body material: aluminum
- mechanical impact protection: IK07
- packaging: 1 pc, box



ZS2612 1/-/-/30
15 31 242 612 ZS2612

- power: 20 W
- luminous flux: 2 200 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220–240 V~
- IP rating: IP65
- beam angle: 120°
- dimensions: 135 × 95 × 28 mm
- supply cable length: 30 cm
- lead-in cable material: rubber
- body material: aluminum
- mechanical impact protection: IK07
- packaging: 1 pc, box



ZS2622 1/-/-/20
15 31 242 622 ZS2622